



Lyden Oil Company

Product Information

Powerline Dex-Cool® Antifreeze

Powerline Dex-Cool® Antifreeze is a pre-charged automotive coolant formulated with nitrite-organic acid technology (NOAT) additives and ethylene glycol to create a high quality product for use in applications requiring a DEX-COOL® type antifreeze/coolant. It offers outstanding protection for all cooling system metallurgies, and has anti-scaling and lubricating properties.

Powerline Dex-Cool® Antifreeze meets the specifications of ASTM D-6210, ASTM D-3306, ASTM D-4985, SAE J1034, and is compatible with GM 6277M.

Typical Properties

Powerline Dex-Cool® Antifreeze

Color	Pink
Specific Gravity, ASTM D-1122	
Concentrate	1.120
50% Dilution	1.060
Freezing Point, °C (°F), ASTM D-1177	
50% Dilution	-36 (-34)
Boiling Point, °C (°F), ASTM D-1120	
50% Dilution	107 (226)
pH of 50% Dilution	7.5-9.5
Silicate, ppm	<100
Corrosion of Aluminum, ASTM D-4340	<0.1 mg/cm ² /week

Lyden Oil Company

30692 Tracy Road
Walbridge, OH 43465
1(800)24-LYDEN
local: (419)666-1948
fax: (419)666-8790
gam@lydenoil.com

3711 LeHarp's Road
Youngstown, OH 44515
1(800)362-9410
local: (330)792-1100
fax: (330)792-1462
lal@lydenoil.com

16275 National Parkway
Lansing, MI 48906
1(800)968-6457
local: (517)485-2285
fax: (517)485-0605
jtr@lydenoil.com

8151 Millis Road
Shelby Township, MI 48317
local: (586)997-1319
fax: (586)997-1352
jcc@lydenoil.com

3249 Wales Ave. NW
Massillon, OH 44646
local: (330)832-7800
fax: (330)832-2787
lal@lydenoil.com

