



# Lyden Oil Company

## ProGuard

### Product Information

#### Witco Mineral Seal Oil

**Witco Mineral Seal Oil** is a hydrotreated 40 neutral distillate. It can be utilized in a variety of applications including aluminum rolling oil, ink oil, and drilling fluids.

#### Typical Properties

##### Witco Mineral Seal Oil

Viscosity, ASTM D-445 cSt at 40 °C	3.9-4.5
Viscosity, ASTM D-2161 SUS at 100 °F	40.9
Flash Point, °C (°F), ASTM D-92	141 (285)
Pour Point, °C (°F), ASTM D-5950	-9 (16)
API Gravity, ASTM D-4052	40.3
Density, lbs/gal	6.87
Sulfur, ppm, ASTM D-7039	50
Color, Saybolt, ASTM D-156	+28
Aromatics, mass %, ASTM D-2549	10
Distillation, °F, ASTM D-86	
IBP	530
5%	546
50%	572
95%	615
EBP	623
Aniline Point, °C, ASTM D-611	88.3

#### Lyden Oil Company

30692 Tracy Road  
Walbridge, OH 43465  
1(800)24-LYDEN  
local: (419)666-1948  
fax: (419)666-8790  
gam@lydenoil.com

3711 LeHarms Road  
Youngstown, OH 44515  
1(800)362-9410  
local: (330)792-1100  
fax: (330)792-1462  
lal@lydenoil.com

16275 National Parkway  
Lansing, MI 48906  
1(800)968-6457  
local: (517)485-2285  
fax: (517)485-0605  
jtr@lydenoil.com

8151 Millis Road  
Shelby Township, MI 48317  
local: (586)997-1319  
fax: (586)997-1352  
jcc@lydenoil.com

3249 Wales Ave. NW  
Massillon, OH 44646  
local: (330)832-7800  
fax: (330)832-2787  
lal@lydenoil.com