

Lyden Oil Company

Page **1** of **8** -

1

2

## **PROGUARD RP 5WD**

SDS Number: 17830

#### PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD RP 5WD
Revision Date:	06/09/2016
SDS Number:	17830
Common Name:	Rust preventative
CAS Number:	Blend
Product Code:	17830
<u>Synonyms:</u>	Oil diluted petroleum based rust preventative

#### **Company Identification:**

<i>Manufactured for:</i> LYDEN OIL COMPANY 3711 LeHarps Drive Youngstown, OH 44515	
For Product Information:	1-330-792-1100
For Emergencies:	1-800-424-9300
CHEMTREC:	1-800-424-9300 or 1-703-527-3887

#### HAZARDS IDENTIFICATION



Signal Word:

## DANGER

Hazard Classes/Categories:

Aspiration hazard, Category 1. Skin irritant, Category 2. Serious eye irritation, Category 2B.



Page 2 of 8 \_\_\_\_\_

# Safety Data Sheet

Lyden Oil Company

	PROGUARD RP 5WD
SDS Number: 17830	
Hazard Statement(s):	
	H304: May be fatal if swallowed and enters airways.
	H315: Causes skin irritation.
	H320: Causes eye irritation.
Precaution Statement(s):	
	P101: If medical advice is needed, have product container or label at
	hand. B102: Keen out of reach of children
	P102: Keep out of reach of children.
	P103: Read label before use.
	P302+352: IF ON SKIN: Wash with plenty of water.
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue
	rinsing.
	P301+310: IF SWALLOWED: Immediately call a POISON
	CENTER/doctor
	P331: Do NOT induce vomiting.
	P405: Store locked up.
	P501: Dispose of contents/container in accordance with
	local/regional/national/international regulation.
Other Hazard Statement(s);	
Other Hazard Statement(s):	Repeated exposure may cause skin dryness or cracking.
	nepeated exposure may cause skill dryness of cracking.

3

COMPOSITION / INFORMATION ON INGREDIENTS

#### Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	>90
Calcium Sulfonate	N/A	2-4
Calcium Oxidate	N/A	1-3

\*Any concentration shown as a range is to protect confidentiality or is due to batch variation.



Lyden Oil Company

**PROGUARD RP 5WD** 

SDS Number: 17830

Page 3 of 8 -

## 4 FIRST AID MEASURES Description of First Aid Measures: Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention. Skin Contact: Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed. Eye Contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention. Ingestion: If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. Symptoms and Effects, both acute and delayed: No further relevent data available. **Recommended Actions:** Treat symptomatically. Call a doctor or poison control center for guidance. FIRE FIGHTING MEASURES 5 **Recommended Fire-Extinguishing Equipment:** Use dry powder, foam, or carbon dioxide fire

Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.



Lyden Oil Company

## Page 4 of 8 -**PROGUARD RP 5WD** SDS Number: 17830 Possible Hazards During a Fire: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. **Recommendations to Firefighters:** No special measures required. 6 ACCIDENTAL RELEASE MEASURES **Personal Precautions:** Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition. **Emergency Procedures:** Contain spilled material, collect in suitable and properly labeled containers. **Environmental Precautions:** Do not allow to reach sewage system or any water course. Do not allow to enter ground waters. Cleanup Procedures: Pick up excess with inert absorbant material. HANDLING AND STORAGE 7 Handling Precautions: Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container.



Lyden Oil Company

### **PROGUARD RP 5WD**

SDS Number: 17830

Page 5 of 8 -

Hot surfaces may ignite the product. Vapors are heavier than air, so they may travel across the ground and reach remote ignition sources. Static electricity may accumulate and create a fire hazard. Bond and ground handling equipment and transfer containers to prevent sparking.

#### Storage Requirements:

Keep container tightly sealed. Keep away from sources of ignition.

#### **EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### **Exposure Limits:**

8

9

-64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic (>90%):

ACGIH TLV – Long-term value: 5mg/m<sup>3</sup> OSHA PEL – Long-term value: 5mg/m<sup>3</sup>

#### **Engineering Controls:**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

#### Personal Protective Equipment:

Wash hands before breaks and at the end of work. Use safety glasses and gloves.

#### PHYSICAL AND CHEMICAL PROPERTIES

Color:	Clear
Physical State:	Liquid
Odor:	Data not available
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	Data not available
Boiling Range:	Data not available
Flash Point:	129.4° C / 264.9° F (TCC Method)



Lyden Oil Company

**PROGUARD RP 5WD** 

#### SDS Number: 17830

Page 6 of 8 -

Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	Data not available
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	6.0 mm²/sec (kinematic at 40° C)

# 10 STABILITY AND REACTIVITY Stability:

<u>Stability.</u>	Stable under normal conditions.
Reactivity:	Not reactive under normal conditions.
Conditions to Avoid:	Extreme temperature, sparks, open flame, and direct sunlight.
Hazardous Reactions:	No known hazardous reactions.
Incompatible Materials:	No further relevant information available.
Decomposition Products:	Hazardous decomposition products are not expected to form.



Lyden Oil Company

**PROGUARD RP 5WD** 

SDS Number: 17830

Page **7** of **8** –

11 TOXICOLOGICAL INFORMATIO	N
Routes of Exposure:	
	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Exposure Effects:	Repeated skin contact may cause dermatitis or an oil acne.
Measures of Toxicity:	No test data available.
Carcinogenic/Mutagenic Precautions:	Non-carcinogenic and not expected to be mutagentic.
12 ECOLOGICAL INFORMATION	
Ecological Precautions:	Avoid exposing to the environment.
Ecological Effects: No specific environmental	or aquatic data available.
13 DISPOSAL CONSIDERATIONS	
Disposal Methods:	Dispose of waste material in accordance with all local, state, and federal requirements.
Disposal Containers:	Use properly approved container for disposal.
Special Precautions:	Do not flush to surface waters or drains.



Lyden Oil Company

SDS Number: 17830

Page 8 of 8 -

14	TRANSPORT	INFORMATION	
- 2-4			
<u>UN Number:</u> <u>UN Shipping Nai</u> <u>Transport Hazar</u>		Data not available Data not available Data not available	
Packing Group:		Data not available	
Environmental F	lazards:		Data not available
Bulk Transport C	<u>Buidance:</u>		Data not available
Special Precaution	ons:		Not regulated by DOT.

#### 15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 OTHER INFORMATION		16	OTHER INFORMATION
----------------------	--	----	-------------------

Last Revision Date: 06/09/2016

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.