

Lyden Oil Company

Page **1** of **8** –

1

2

PROGUARD Natural Gas Engine Oil LA 15W-40

SDS Number: 17834

PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD Natural Gas Engine Oil LA 15W-40
Revision Date:	03/04/2016
SDS Number:	17834
Common Name:	Heavy Paraffinic Oil
CAS Number:	Blend
Product Code:	17834
Synonyms:	Lubricant for natural gas powered engines

Company Identification:

Manufactured for:LYDEN OIL COMPANY3711 LeHarps DriveYoungstown, OH 44515For Product Information:1-330-792-1100For Emergencies:1-800-424-9300CHEMTREC:1-800-424-9300 or 1-703-527-3887

HAZARDS IDENTIFICATION



Signal Word:

WARNING

Hazard Classes/Categories:

Skin corrosive, Category 1A. Serious eye irritation, Category 2A. Hazardous to the aquatic environment, Category chronic 3.



Page 2 of 8 —

SDS Number: 17834

Safety Data Sheet

Lyden Oil Company

PROGUARD Natural Gas Engine Oil LA 15W-40

Hazard Statement(s):	
	H317: May cause an allergic skin reaction.
	H319: Causes serious eye irritation.
	H412: Harmful to aquatic life with long-lasting effects.
Precaution Statement(s):	
	P101: If medical advice is needed, have product container or label at
	hand. D102: Keen out of reach of shildren
	P102: Keep out of reach of children.
	P103: Read label before use.
	P302+352: IF ON SKIN: Wash with plenty of water.
	P305+351+338: IF IN EYES: Rinse cautiously with water for several
	minutes. Remove contact lenses if present and easy to do – continue
	rinsing.
	P273: Avoid release to the environment.
Other Hazard Statement(s):	
	-NFPA Ratings:
	Health = 1
	Fire = 1
	Reactivity = 0

3

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Petroleum, heavy paraffinic oil	64742-65-0	70-90
Additives	N/A	5-15
Zinc alkyldithiophosphate	N/A	<1

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.



PROGUARD Natural Gas Engine Oil LA 15W-40

Lyden Oil Company

SDS Number: 17834

Page 3 of 8 -

4 FIRST AID MEASURES Description of First Aid Measures: Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention. Skin Contact: Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed. Eye Contact: Flush with water for several minutes. If effects occur, consult a physician. Ingestion: Rinse mouth with water. If symptoms develope, obtain medical attention. Symptoms and Effects, both acute and delayed: No further relevent data available. **Recommended Actions:** Treat symptomatically. Call a doctor or poison control center for guidance. 5 FIRE FIGHTING MEASURES **Recommended Fire-Extinguishing Equipment:** Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.



Lyden Oil Company

Page 4 of 8	Lyden on company
	PROGUARD Natural Gas Engine Oil LA 15W-40
SDS Number: 17834	
Possible Hazards During a Fire:	
	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Recommendations to Firefighters:	
	Proper protective equipment including breathing apparatus.
6 ACCIDENTAL RELEASE MEASU	IRES
Personal Precautions:	
	Avoid contact with skin, eyes, and clothing.
Emergency Procedures:	Contain spilled material, collect in suitable and properly labeled containers.
Environmental Precautions:	Do not allow to reach sewage system or any water course. Do not allow to enter ground waters.
<u>Cleanup Procedures:</u>	Pick up excess with inert absorbant material.
7 HANDLING AND STORAGE	
Handling Precautions:	Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container.
<u>Storage Requirements:</u>	Keep container tightly sealed. Keep away from sources of ignition.



Lyden Oil Company

Page **5** of **8** –

PROGUARD Natural Gas Engine Oil LA 15W-40

SDS Number: 17834

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

Petroleum, heavy paraffinic oil :

ACGIH TWA – 5mg/m³ (oil mist) ACGIH STEL - 10mg/m³ (oil mist) OSHA TWA – 5mg/m³ (oil mist)

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work. Use safety glasses and gloves.

9

PHYSICAL AND CHEMICAL PROPERTIES

Physical State:LiquidOdor:Data not availableOdor Threshold:Data not availablepH:Data not availableMelting Point:Data not availableBoiling Point:Data not available
Odor Threshold:Data not availablepH:Data not availableMelting Point:Data not available
pH: Data not available Melting Point: Data not available
Melting Point: Data not available
-
Boiling Point: Data not available
Boiling Range: Data not available
Flash Point: >185° C / >365° F (COC Method)
Evaporation Rate: Data not available
Flammability: Data not available
Flammability Limits: Data not available
Vapor Pressure: Data not available
Vapor Density: Data not available
Relative Density: Data not available
Solubilities: Insoluble in water
Partition Coefficient: Data not available
Auto-Ignition Temperature: Data not available
Decomposition Temperature: Data not available
Viscosity: 13.8 mm ² /sec (kinematic at 100° C)



PROGUARD Natural Gas Engine Oil LA 15W-40

Lyden Oil Company

SDS Number: 17834

Page 6 of 8 -

10 STABILITY AND REACTIVITY Stability: Stable under normal conditions. **Reactivity:** Not reactive under normal conditions. Conditions to Avoid: Extreme temperature, sparks, open flame, and direct sunlight. Hazardous Reactions: No known hazardous reactions. Incompatible Materials: Strong oxidizers and strong reducing agents. **Decomposition Products:** Oxides of carbon and hydrogen. TOXICOLOGICAL INFORMATION 11 Routes of Exposure: Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Exposure Effects: Repeated skin contact may cause dermatitis or an oil acne.

Measures of Toxicity:

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be mutagentic.

No test data available.



PROGUARD Natural Gas Engine Oil LA 15W-40

Lyden Oil Company

SDS Number: 17834

Page 7 of 8 -

12	ECOLOGICAL INFORMATION	
Ecological Preca	utions:	Avoid exposing to the environment.
Ecological Effect	<u>s:</u> No specific environmental	or aquatic data available.
13	DISPOSAL CONSIDERATIONS	
Disposal Method		Dispose of waste material in accordance with all local, state, and federal requirements.
<u>Disposal Contain</u>	<u>iers:</u>	Use properly approved container for disposal.
Special Precaution	ons:	Do not flush to surface waters or drains.
14	TRANSPORT INFORMATION	
UN Number: UN Shipping Nar Transport Hazar Packing Group:	Data not available <u>me:</u> Data not available	
Environmental H	lazards:	Data not available
Bulk Transport G	Guidance:	Data not available

Special Precautions:

Not regulated by DOT.



Lyden Oil Company

Page 8 of 8 -

PROGUARD Natural Gas Engine Oil LA 15W-40

SDS Number: 17834

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

Contains Zinc compounds required to be reported per SARA Section 313. Contains < 1% Zn.

16 OTHER INFORMATION

Last Revision Date: 03/04/2016

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.