

Lyden Oil Company

Page 1 of 8 -

1

2

PROGUARD Multi-Vehicle ATF Synthetic Blend

SDS Number: 17838

PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD Multi-Vehicle ATF Synthetic Blend
Revision Date:	12/11/2015
SDS Number:	17838
Common Name:	Multi-Vehicle ATF
CAS Number:	Blend
Product Code:	17838
<u>Synonyms:</u>	Automatic transmission fluid, Petroleum based lubricant

Company Identification:

<i>Manufactured for:</i> LYDEN OIL COMPANY 3711 LeHarps Road Youngstown, OH 44515	
For Product Information:	1-330-792-1100
For Emergencies:	1-800-424-9300
CHEMTREC:	1-800-424-9300 or 1-703-527-3887

None

HAZARDS IDENTIFICATION

Signal Word:	None
Hazard Classes/Categories:	Environmental, Hazards to the aquatic environment - Chronic, Category 3.
Hazard Statement(s):	H412: Harmful to aquatic life with long-lasting effects.
<u>Precaution Statement(s):</u>	P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use. P273: Avoid release to the environment.



Lyden Oil Company

Page 2 of 8 -

PROGUARD Multi-Vehicle ATF Synthetic Blend

SDS Number: 17838

Other Hazard Statement(s):

-NFPA Ratings: Health = 0 Fire = 1 Reactivity = 0

Repeated exposure may cause skin dryness or cracking.

3

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	75-85
Methacrylate Copolymer	N/A	5-15
Polyolefin amide alkeneamine	N/A	2-5
Additives	N/A	20-25

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4	FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:	If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.
Eye Contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention.



Lyden Oil Company

Page 3 of 8	
	PROGUARD Multi-Vehicle ATF Synthetic Bler
SDS Number: 17838	
Ingestion:	
-	ith water. Drink one or two glasses of water and DO
	miting. Obtain medical attention.
Symptoms and Effects, both acute and delayed:	
	No further relevent data available.
Recommended Actions:	
	Treat symptomatically. Call a doctor or poison
	control center for guidance.
5 FIRE FIGHTING MEASURES	
Recommended Fire-Extinguishing Equipment:	
	Use dry powder, foam, or carbon dioxide fire
	extinguishers. Water may be ineffective in fighting
	an oil fire unless used by experienced fire fighters.
Dossible Hazards During a Fire	
Possible Hazards During a Fire:	Hazardous combustion products may include: A
	complex mixture of airborne solid and liquid
	particulates and gases (smoke). Carbon monoxide.
	Unidentified organic and inorganic compounds.
Pacammandations to Eirofightars:	
Recommendations to Firefighters:	Proper protective equipment including breathing
	apparatus.
6 ACCIDENTAL RELEASE MEASU	IRES
Personal Precautions:	

Avoid contact with skin, eyes, and clothing. Avoid breathing vapors. Keep away from sources of ignition.



Lyden Oil Company

Page 4 of 8	
C	PROGUARD Multi-Vehicle ATF Synthetic Blend
SDS Number: 17838	
Emergency Procedures:	Contain spilled material, collect in suitable and properly labeled containers.
Environmental Precautions:	Do not allow to reach sewage system or any water course. Do not allow to enter ground waters.
<u>Cleanup Procedures:</u>	Pick up excess with inert absorbant material. Treat contaminated absorbent same as spilled product.
7 HANDLING AND STORAGE	
Handling Precautions:	Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container. Ensure all equipment is electrically grounded before beginning transfer operations.
Storage Requirements:	Keep container tightly sealed. Keep away from sources of ignition.
8 EXPOSURE CONTROLS / PERS	ONAL PROTECTION
Exposure Limits: No data available.	
Engineering Controls:	All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).
Personal Protective Equipment:	Wash hands before breaks and at the end of work. Use safety glasses and gloves.



Lyden Oil Company

SDS Number: 17838

Page 5 of 8 -

PROGUARD Multi-Vehicle ATF Synthetic Blend

9 PHYSICAL AND CHEMICAL PROPERTIES Color: Red Physical State: Liquid Oder: Data not available

Odor:	Data not available
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	-40° F pour point
Boiling Point:	Data not available
Boiling Range:	Data not available
Flash Point:	217.8° C / 424° F (COC Method)
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	7.21 pounds per gallon at 60° F
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	Data not available

.0	STABILITY AND REACTIVITY

<u>Stability:</u>	Stable under normal conditions.
Reactivity:	Not reactive under normal conditions.
Conditions to Avoid:	Extreme temperature, sparks, open flame, and direct sunlight.
Hazardous Reactions:	No known hazardous reactions.



Lyden Oil Company

PROGUARD Multi-Vehicle ATF Synthetic Blend
No further relevant information available.
Hazardous decomposition products are not expected to form.
DN
Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Repeated skin contact may cause dermatitis or an oil acne.
No test data available.
Non-carcinogenic and not expected to be mutagentic.
Avoid exposing to the environment.
al or aquatic data available.



PROGUARD Multi-Vehicle ATF Synthetic Blend

Lyden Oil Company

SDS Number: 17838

Page 7 of 8 -

13 DISPOSAL C	ONSIDERATIONS		
Disposal Methods:			
		Dispose of waste material in accordance with all local, state, and federal requirements.	
Disposal Containers:			
		Use properly approved container for disposal.	
Special Precautions:		Do not flush to surface waters or drains.	
14 TRANSPORT	INFORMATION		
UN Number:	Data not available		
UN Shipping Name:	Data not available		
<u>Transport Hazard Class:</u> Packing Group:	Data not available Data not available		
Environmental Hazards:			
		Data not available	
Bulk Transport Guidance:		Data not available	
Special Precautions:		Not regulated by DOT.	
15 REGULATOR	Y INFORMATION		

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.



Lyden Oil Company

Page 8 of 8 -

PROGUARD Multi-Vehicle ATF Synthetic Blend

SDS Number: 17838

16

Last Revision Date: 12/11/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.