

Lyden Oil Company

Page 1 of 8 -

**PROGUARD Mist Lube 320** 

SDS Number: 17849

#### PRODUCT AND COMPANY INFORMATION

Product Name: PROGUARD Mist Lube 320

<u>Revision Date:</u> 09/22/2015 SDS Number: 17849

<u>Common Name:</u> Hydrotreated Heavy Paraffinic Oil

<u>CAS Number:</u> Blend <u>Product Code:</u> 17849

Synonyms: Petroleum based lubricant

### **Company Identification:**

Manufactured for: LYDEN OIL COMPANY 3711 LeHarps Road Youngstown, OH 44515

For Product Information: 1-330-792-1100 For Emergencies: 1-800-424-9300

CHEMTREC: 1-800-424-9300 or 1-703-527-3887

### HAZARDS IDENTIFICATION



Signal Word: WARNING

**Hazard Classes/Categories:** 

Serious eye irritation, Category 2B.

Skin irritant, Category 3.

Reproductive toxicity, Category 2.

Hazardous to the aquatic environment, Category chronic 1.



Lyden Oil Company

Page 2 of 8 -

**PROGUARD Mist Lube 320** 

SDS Number: 17849

Hazard Statement(s):

H320: Causes eye irritation.

H316: Causes mild skin irritation.

H361: Suspected of damaging fertility or the unborn child. H410: Very toxic to aquatic life with long-lasting effects.

Precaution Statement(s):

P101: If medical advice is needed, have product container or label at

hand.

P102: Keep out of reach of children.

P103: Read label before use.

P273: Avoid release to the environment.

P302+352: IF ON SKIN: Wash with plenty of soap and water. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue

rinsing.

Other Hazard Statement(s):

Repeated exposure may cause skin dryness or cracking.

# Ingredients:

COMPOSITION / INFORMATION ON INGREDIENTS

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	5-15
Residual oils, petroleum, solvent dewaxed	64742-62-7	85-95
Polyisobutylene	9003-27-4	<3
Tricresyl phosphate	1330-78-5	<1
Di-t-butyl-p-cresol	128-37-0	<1
Alkenyl carboxylic acid	Proprietary	<1

<sup>\*</sup>Any concentration shown as a range is to protect confidentiality or is due to batch variation.



Lyden Oil Company

Page **3** of **8** —

**PROGUARD Mist Lube 320** 

SDS Number: 17849

### 4 FIRST AID MEASURES

#### **Description of First Aid Measures:**

Inhalation:

If symptoms develop, move victim to fresh air. If symptoms persist,

obtain medical attention.

Skin Contact:

Wash with soap and water. Remove contaminated clothing and wash

before reuse. Get medical attention if needed.

Eye Contact:

Rinse opened eye for several minutes under running water. If

symptoms persist, consult medical attention.

Ingestion:

Rinse mouth with water. If symptoms develop, obtain medical

attention.

Symptoms and Effects, both acute and delayed:

No further relevent data available.

**Recommended Actions:** 

Treat symptomatically. Call a doctor or poison

control center for guidance.

#### FIRE FIGHTING MEASURES

#### Recommended Fire-Extinguishing Equipment:

Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.



Lyden Oil Company

Page 4 of 8 —

**PROGUARD Mist Lube 320** 

SDS Number: 17849

Possible Hazards During a Fire:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Recommendations to Firefighters:

No special measures required.

#### ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** 

Avoid contact with skin, eyes, and clothing.

Keep away from sources of ignition.

**Emergency Procedures:** 

Contain spilled material, collect in suitable and

properly labled containers.

**Environmental Precautions:** 

Do not allow to reach sewage system or any water

course.

Do not allow to enter ground waters.

Cleanup Procedures:

Pick up excess with inert absorbant material.

### HANDLING AND STORAGE

**Handling Precautions:** 

Handle with care and avoid spillage on the floor.

Do not cut, weld, drill, grind, braze, or solder

container.

**Storage Requirements:** 

Keep container tightly sealed.

Keep away from sources of ignition.



Lyden Oil Company

Page **5** of **8** -

### **PROGUARD Mist Lube 320**

SDS Number: 17849

### EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Exposure Limits:**

-64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic (5-15%):

ACGIH TLV – Long-term value: 5mg/m<sup>3</sup> OSHA PEL – Long-term value: 5mg/m<sup>3</sup>

-64742-62-7 Residual oils, petroleum, solvent dewaxed (85-95%):

ACGIH TWA – 5mg/m³ (oil mist) ACGIH STEL - 10mg/m³ (oil mist) OSHA TWA – 5mg/m³ (oil mist)

-128-37-0 Di-t-butyl-p-cresol (<1%):

ACGIH TLV - 10 mg/m<sup>3</sup> NIOSH REL - 10 mg/m<sup>3</sup>

**Engineering Controls:** 

All ventilation should be designed in accordance

with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work.

Use safety glasses and gloves.

#### 9 PHYSICAL AND CHEMICAL PROPERTIES

Color: Amber Physical State: Liquid

Odor: Data not available
Odor Threshold: Data not available
pH: Data not available
Melting Point: Data not available

Boiling Point: >425° F

Boiling Range:

Flash Point:

Evaporation Rate:

Data not available

Data not available

Data not available

Data not available



Lyden Oil Company

Page **6** of **8** -

**PROGUARD Mist Lube 320** 

SDS Number: 17849

Flammability Limits: Data not available Vapor Pressure: Data not available Vapor Density: Data not available Relative Density: 0.87 (where water = 1) Solubilities: Insoluble in water Partition Coefficient: Data not available Auto-Ignition Temperature: Data not available **Decomposition Temperature:** Data not available

Viscosity: 320 mm<sup>2</sup>/sec (kinematic at 40° C)

### 10 STABILITY AND REACTIVITY

Stability:

Stable under normal conditions.

**Reactivity:** 

Not reactive under normal conditions.

Conditions to Avoid:

Extreme temperature, sparks, open flame, and

direct sunlight.

**Hazardous Reactions:** 

No known hazardous reactions.

**Incompatible Materials:** 

No further relevant information available.

**Decomposition Products:** 

Hazardous decomposition products are not

expected to form.

#### 11 TOXICOLOGICAL INFORMATION

#### **Routes of Exposure:**

Skin, inhalation, and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.



Lyden Oil Company

Page **7** of **8** —

**PROGUARD Mist Lube 320** 

SDS Number: 17849

**Exposure Effects:** 

Repeated skin contact may cause dermatitis or an

oil acne.

**Measures of Toxicity:** 

No test data available.

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be

mutagentic.

12 ECOLOGICAL INFORMATION

**Ecological Precautions:** 

Avoid exposing to the environment.

**Ecological Effects:** 

No specific environmental or aquatic data available.

13 DISPOSAL CONSIDERATIONS

**Disposal Methods:** 

Dispose of waste material in accordance with all

local, state, and federal requirements.

<u>Disposal Containers:</u>

Use properly approved container for disposal.

**Special Precautions:** 

Do not flush to surface waters or drains.

14 TRANSPORT INFORMATION

UN Number:Data not availableUN Shipping Name:Data not availableTransport Hazard Class:Data not availablePacking Group:Data not available



Lyden Oil Company

PROGUARD Mist Lube 320

SDS Number: 17849

Environmental Hazards:

Data not available

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 OTHER INFORMATION

Last Revision Date: 09/22/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.