

Lyden Oil Company

Page **1** of **7** –

1

PROGUARD EP 46 Gear Oil

SDS Number: 17865

PRODUCT AND COMPANY INFORMATION

| Product Name: | PROGUARD EP 46 Gear Oil |
|------------------|-------------------------------------|
| Revision Date: | 03/01/2016 |
| SDS Number: | 17865 |
| Common Name: | Petroleum, heavy paraffinic oil |
| CAS Number: | Blend |
| Product Code: | 17865 |
| <u>Synonyms:</u> | Petroleum based lubricant, Gear oil |

Company Identification:

Manufactured for:LYDEN OIL COMPANY3711 LeHarps DriveYoungstown, OH 44515For Product Information:1-330-792-1100For Emergencies:1-800-424-9300CHEMTREC:1-800-424-9300 or 1-703-527-3887

2 HAZARDS IDENTIFICATION

| Signal Word: | None |
|----------------------------|--|
| Hazard Classes/Categories: | None |
| Hazard Statement(s): | None |
| Precaution Statement(s): | P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use. |



Lyden Oil Company

Page 2 of 7 —

PROGUARD EP 46 Gear Oil

SDS Number: 17865

Other Hazard Statement(s):

Repeated skin contact may cause dermatitis or an oil acne.

3 COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

| Chemical Name | CAS Number | Percentage |
|---|------------|------------|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | 64742-65-0 | >95 |
| Olefin Sulfide | N/A | <2 |
| Alkenyl Amine | N/A | <0.1 |

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

| | 4 | FIRST AID MEASURES |
|--|---|--------------------|
|--|---|--------------------|

Description of First Aid Measures:

| Inhalation: | If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention. |
|---------------|--|
| Skin Contact: | Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed. |
| Eye Contact: | Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention. |
| Ingestion: | Rinse mouth with water. If symptoms develop, obtain medical attention. |

Symptoms and Effects, both acute and delayed:

No further relevent data available.



PROGUARD EP 46 Gear Oil

Lyden Oil Company

| SDS Number: 2 | 17865 |
|---------------|-------|
|---------------|-------|

Page **3** of **7** —

Recommended Actions:

Treat symptomatically. Call a doctor or poison control center for guidance.

| 5 FIRE FIGHTING MEASURES | |
|---|---|
| Recommended Fire-Extinguishing Equipment: | |
| | Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters. |
| Possible Hazards During a Fire: | |
| | Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. |
| | |
| Recommendations to Firefighters: | No special measures required. |
| | |
| | IRES |
| 6 ACCIDENTAL RELEASE MEASU | JRES |
| 6 ACCIDENTAL RELEASE MEASU Personal Precautions: | JRES Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition. |
| | Avoid contact with skin, eyes, and clothing. |
| Personal Precautions: | Avoid contact with skin, eyes, and clothing. |
| Personal Precautions: Emergency Procedures: | Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition. Contain spilled material, collect in suitable and |
| Personal Precautions: | Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition. Contain spilled material, collect in suitable and |



PROGUARD EP 46 Gear Oil

Lyden Oil Company

SDS Number: 17865

Page 4 of 7 —

Cleanup Procedures:

Pick up excess with inert absorbant material.

7 HANDLING AND STORAGE Handling Precautions:

> Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container.

Storage Requirements:

Keep container tightly sealed. Keep away from sources of ignition.

8

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

-64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic (>95%):

ACGIH TLV – Long-term value: 5mg/m³ OSHA PEL – Long-term value: 5mg/m³

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work. Use safety glasses and gloves.

9

PHYSICAL AND CHEMICAL PROPERTIES

Color: Physical State: Odor: Odor Threshold: pH: Amber Liquid Data not available Data not available Data not available



PROGUARD EP 46 Gear Oil

Lyden Oil Company

SDS Number: 17865

Page 5 of 7 -

10

| Melting Point: |
|----------------------------|
| Boiling Point: |
| Boiling Range: |
| Flash Point: |
| Evaporation Rate: |
| Flammability: |
| Flammability Limits: |
| Vapor Pressure: |
| Vapor Density: |
| Relative Density: |
| Solubilities: |
| Partition Coefficient: |
| Auto-Ignition Temperature: |
| Decomposition Temperature: |
| Viscosity: |

Data not available Data not available Data not available 176.7° C / 350.1° F (TCC method) Data not available Insoluble in water Data not available Ata not available

STABILITY AND REACTIVITY

| <u>Stability:</u> | Stable under normal conditions. |
|-----------------------------|---|
| <u>Reactivity:</u> | Not reactive under normal conditions. |
| <u>Conditions to Avoid:</u> | Extreme temperature, sparks, open flame, and direct sunlight. |
| Hazardous Reactions: | No known hazardous reactions. |
| Incompatible Materials: | No further relevant information available. |
| Decomposition Products: | Hazardous decomposition products are not expected to form. |



PROGUARD EP 46 Gear Oil

Lyden Oil Company

SDS Number: 17865

| 11 TOXICOLOGICAL INFORMATION | N |
|--|---|
| Routes of Exposure: | |
| | Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion. |
| Exposure Effects: | |
| | Repeated skin contact may cause dermatitis or an oil acne. |
| Measures of Toxicity: | No test data available. |
| Carcinogenic/Mutagenic Precautions: | |
| | Non-carcinogenic and not expected to be mutagentic. |
| | |
| 12 ECOLOGICAL INFORMATION | |
| Ecological Precautions: | Avoid exposing to the environment. |
| Ecological Effects: No specific environmental | or aquatic data available. |
| | |
| 13 DISPOSAL CONSIDERATIONS | |
| Disposal Methods: | |
| <u> </u> | Dispose of waste material in accordance with all local, state, and federal requirements. |
| Disposal Containers: | Use properly approved container for disposal. |
| Special Precautions: | Do not flush to surface waters or drains. |

Page **6** of **7** –



Lyden Oil Company

SDS Number: 17865

Page 7 of 7 -

| PROGUARD E | P 46 Gear Oil |
|-------------------|---------------|
|-------------------|---------------|

| 14 | TRANSPORT | INFORMATION | |
|------------------------|------------------|--------------------|-----------------------|
| | | | |
| <u>UN Number:</u> | | Data not available | |
| UN Shipping Nar | <u>ne:</u> | Data not available | |
| Transport Hazar | d Class: | Data not available | |
| Packing Group: | | Data not available | |
| <u>Environmental H</u> | lazards: | | Data not available |
| Bulk Transport G | <u>iuidance:</u> | | Data not available |
| Special Precaution | ons: | | Not regulated by DOT. |

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

| 16 OTHER INFORMATION | |
|----------------------|--|
|----------------------|--|

Last Revision Date: 03/01/2016

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.