

Lyden Oil Company

Page **1** of **8** –

1

PROGUARD MeritCut 1000

SDS Number: 17885

PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD MeritCut 1000
Revision Date:	09/22/2015
SDS Number:	17885
Common Name:	Hydrotreated heavy naphthenic oil
CAS Number:	Blend
Product Code:	17885
<u>Synonyms:</u>	Cutting fluid

Company Identification:

<i>Manufactured for:</i> LYDEN OIL COMPANY 3711 LeHarps Road Youngstown, OH 44515	
For Product Information:	1-330-792-1100
For Emergencies:	1-800-424-9300
CHEMTREC:	1-800-424-9300 or 1-703-527-3887

HAZARDS IDENTIFICATION



Signal Word:

2

WARNING

Hazard Classes/Categories:

Skin sensitization, Category 1.

Hazard Statement(s):

H317: May cause an allergic skin reaction.



Lyden Oil Company

SDS Number: 17885

Page 2 of 8 -

PROGUARD MeritCut 1000

Precaution Statement(s):	
	P101: If medical advice is needed, have product container or label at
	hand.
	P102: Keep out of reach of children.
	P103: Read label before use.
	P261: Avoid breathing dust/fumes/gas/mist/vapors/spray.
	P272: Contaminated work clothing should not be allowed out of the workplace.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P302+352: IF ON SKIN: Wash with plenty of soap and water.
	P333+313: If skin irritation or a rash occurs: Get medical advice/attention.
	P363: Wash contaminated clothing before reuse. P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

Other Hazard Statement(s):

Repeated exposure may cause skin dryness or cracking.

3 COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
4(2-Nitrobutyl)Morpholine	2224-44-4	Proprietary

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:

If inhaled, move victim to fresh air. If victim has stopped breathing, give artificial respiration, preferably, mouth-to-mouth. Seek immediate medical attention.



Lyden Oil Company

Page 3 of 8		Lyden on company
		PROGUARD MeritCut 1000
SDS Number: 17885		
Skin Contact:		o and water. Remove contaminated clothing and wash iet medical attention if needed.
Eye Contact:		
	-	ye for at least 15 minutes under running water. Do not rub eyes. If irritation develops, consult medical
Ingestion:		
	Rinse mouth wind attention.	ith water. If symptoms develop, obtain medical
Symptoms and Effects, both	acute and delayed:	No further relevent data available.
<u>Recommended Actions:</u>		Treat symptomatically. Call a doctor or poison control center for guidance.
5 FIRE FIGH	TING MEASURES	
Recommended Fire-Extingui	ishing Equipment:	Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.
Possible Hazards During a Fi	<u>re:</u>	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Recommendations to Firefig	<u>hters:</u>	No special measures required.



PROGUARD MeritCut 1000

Lyden Oil Company

SDS Number: 17885

Page 4 of 8 -

6 ACCIDENTAL RELEASE MEASUR	RES
Personal Precautions:	
	Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition.
Emergency Procedures:	Contain spilled material, collect in suitable and properly labled containers.
Environmental Precautions:	
	Do not allow to reach sewage system or any water course. Do not allow to enter ground waters.
<u>Cleanup Procedures:</u>	Pick up excess with inert absorbant material.
7 HANDLING AND STORAGE	
Handling Precautions:	Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container.
Storage Requirements:	
	Store in closed containers in a cool, dry well ventilated area not exposed to sunlight. Maintain closure of bungs. Store at temperatures between 5°C and 30°C. Do not reuse container. Avoid container damage while storing. Empty containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, bronze, solder, drill, grind or expose such containers to heat, flame, sparks, static electricity or other sources of ignition; they may explode and cause injury or death. Do not attempt to refill containers since residue is difficult to remove. Empty drums should be completely drained, properly bunged and



Lyden Oil Company

SDS Number: 17885

Page 5 of 8 -

PROGUARD MeritCut 1000

returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner in accordance with governmental regulations.

EXPOS

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

-Distillates (petroleum), severely hydrotreated heavy naphthenic:

ACGIH TLV $- 5mg/m^3$ (oil mist)

-102-71-6 Triethanolamine:

ACGIH TLV – 5mg/m³

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Respiratory protection: General room ventilation should be satisfactory. Exhaust ventilation may be necessary if misting is generated.

Eye protection: No eye protection is needed under conditions of normal use. If there is a possibility that the product can be splashed into the eyes, then safety glasses with side shields or chemical goggles are required. Contact lenses should also not be worn if the product could be splashed into the eyes.

Hand protection: No gloves are required for single, short duration exposures. For prolonged or repeated exposures, wear rubber gloves.

Body protection: If product use involves single, short duration exposures, then no additional protective wear for covering the skin is required. For prolonged or repeated exposures to the skin, wear impervious, protective clothing including rubber safety shoes to avoid skin contact

8



Lyden Oil Company

Page 6 of 8 -

PROGUARD MeritCut 1000

SDS Number: 17885

9 PHYSICAL AND C	CHEMICAL PROPERTIES
Color:	Amber
Physical State:	Liquid
Odor:	Data not available
Odor Threshold:	Data not available
pH:	9.0
Melting Point:	Data not available
Boiling Point:	>105° C
Boiling Range:	Data not available
Flash Point:	355° F (COC Method)
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	0.945 at 15.5° C
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	Data not available

10	STABILITY AND REACTIVITY	
<u>Stability:</u>		Stable under normal conditions.
<u>Reactivity:</u>		Not reactive under normal conditions.
Conditions to Av	void:	Extreme temperature, sparks, open flame, and direct sunlight.

Hazardous Reactions:

Incompatible Materials:

Strong oxidizers.

No known hazardous reactions.



Lyden Oil Company

Page 7 of 8 ——		
		PROGUARD MeritCut 1000
SDS Number: 178	85	
Decomposition Pr	oducts:	
		Hazardous decomposition products are not expected to form.
11		ON
Routes of Exposur		
Noules of Exposur	<u>e.</u>	Skin, inhalation, and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Exposure Effects:		Repeated skin contact may cause dermatitis or an oil acne.
Measures of Toxic	sity:	
		No test data available.
Carcinogenic/Mut	agenic Precautions:	
		Non-carcinogenic and not expected to be mutagentic.
12	ECOLOGICAL INFORMATION	
12		
Ecological Precaut	<u>ions:</u>	Avoid exposing to the environment.
Ecological Effects:		al or aquatic data available.
13	DISPOSAL CONSIDERATIONS	
Disposal Methods	<u>:</u>	

Dispose of waste material in accordance with all local, state, and federal requirements.

Disposal Containers:

Use properly approved container for disposal.



Lyden Oil Company

Page **8** of **8** –

PROGUARD MeritCut 1000

SDS Number: 17885

Special Precautions:

Do not flush to surface waters or drains.

14	TRANSPORT I	INFORMATION	
<u>UN Number:</u>		Data not available	
UN Shipping Nar	<u>me:</u>	Data not available	
Transport Hazar	d Class:	Data not available	
Packing Group:		Data not available	
Environmental F	<u>lazards:</u>		Data not available
Bulk Transport G	Guidance:		Data not available
Special Precaution	ons:		Not regulated by DOT.

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 OTHER INFORMATION	
----------------------	--

Last Revision Date: 09/22/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.