

Lyden Oil Company

Page 1 of 7 -

1

2

## PROGUARD EC AW 46 Hydraulic Fluid

SDS Number: 17891

#### PRODUCT AND COMPANY INFORMATION

PROGUARD EC AW 46 Hydraulic Fluid
08/13/2015
17891
Hydrotreated heavy paraffinic oil
Blend
17891
Zinc free antiwear hydraulic fluid

#### **Company Identification:**

<i>Manufactured for:</i> LYDEN OIL COMPANY 3711 LeHarps Road Youngstown, OH 44515	
For Product Information:	1-330-792-1100
For Emergencies:	1-800-424-9300
CHEMTREC:	1-800-424-9300 or 1-703-527-3887

### HAZARDS IDENTIFICATION



Signal Word:

WARNING

Hazard Classes/Categories:

Skin irritant, Category 2. Hazardous to the aquatic environment, Category chronic 2.



Lyden Oil Company

Page 2 of 7 \_\_\_\_\_

### **PROGUARD EC AW 46 Hydraulic Fluid**

SDS Number: 17891

Hazard Statement(s):	H315: Causes skin irritation.
	H411: Toxic to aquatic life with long-lasting effects.
Precaution Statement(s):	
	P101: If medical advice is needed, have product container or label at
	hand.
	P102: Keep out of reach of children.
	P103: Read label before use.
	P302+352: IF ON SKIN: Wash with plenty of water
	P273: Avoid release to the environment.
Other Hazard Statement(s):	Departed skip contact may cause dermatitis ar an ail acro

Repeated skin contact may cause dermatitis or an oil acne.

### 3 COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	>95
Additives	N/A	<2

\*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4	FIRST AID MEASURES		
Description of Fi	rst Aid Measures:		
Inhalatio	on: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.		
Skin Cor	ntact: Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.		



Lyden Oil Company

Page <b>3</b> of <b>7</b>		
		PROGUARD EC AW 46 Hydraulic Flu
SDS Number: 17891		
Eye Contact:		ye for several minutes under running water. If ist, consult medical attention.
Ingestion:	Rinse mouth wi attention.	ith water. If symptoms develop, obtain medical
Symptoms and Effects, both a	cute and delayed:	No further relevent data available.
Recommended Actions:		Treat symptomatically. Call a doctor or poison control center for guidance.
5 FIRE FIGHT	ING MEASURES	
Recommended Fire-Extinguis	hing Equipment:	Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.
Possible Hazards During a Fire	<u>::</u>	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
<u>Recommendations to Firefigh</u>	<u>ters:</u>	No special measures required.
6 ACCIDENTA	L RELEASE MEASU	RES

Personal Precautions:

Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition.



Lyden Oil Company

Page <b>4</b> of <b>7</b>		
	PROGUARD EC AW 46 Hydraulic Fluid	
SDS Number: 17891		
Emergency Procedures:	Contain spilled material, collect in suitable and properly labeled containers.	
Environmental Precautions:	Do not allow to reach sewage system or any water course.	
	Do not allow to enter ground waters.	
Cleanup Procedures:	Pick up excess with inert absorbant material.	
7 HANDLING	G AND STORAGE	
Handling Precautions:	Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container.	
Storage Requirements:	Keep container tightly sealed. Keep away from sources of ignition.	
8 EXPOSURE	E CONTROLS / PERSONAL PROTECTION	
Exposure Limits: -6474	-64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic (>95%):	
	H TLV – Long-term value: 5mg/m³ A PEL – Long-term value: 5mg/m³	
Engineering Controls:	All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).	
Personal Protective Equipme		

Personal Protective Equipment:

Wash hands before breaks and at the end of work. Use safety glasses and gloves.



Lyden Oil Company

SDS Number: 17891

Page 5 of 7 –

## **PROGUARD EC AW 46 Hydraulic Fluid**

# 9 PHYSICAL AND CHEMICAL PROPERTIES

Color:	Amber
Physical State:	Liquid
Odor:	Data not available
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	>425° F
Boiling Range:	Data not available
Flash Point:	248.9° C / 480° F (PMCC method)
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	7.165 pounds per gallon at 60° F
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	46 mm <sup>2</sup> /sec (kinematic at 40° C)

10	STABILITY AND REACTIVITY	
<u>Stability:</u>	Stable under normal conditi	ons.
<u>Reactivity:</u>	Not reactive under normal of	onditions.
Conditions to Av	Avoid: Extreme temperature, spark direct sunlight.	s, open flame, and
Hazardous Reac	actions: No known hazardous reactio	ons.
Incompatible Ma	<u>Materials:</u> No further relevant informa	tion available.



**PROGUARD EC AW 46 Hydraulic Fluid** 

Lyden Oil Company

SDS	Number:	17891	

Page 6 of 7 —

**Decomposition Products:** 

Hazardous decomposition products are not expected to form.

11 TOXI	TOXICOLOGICAL INFORMATION		
Routes of Exposure:			
	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.		
Exposure Effects:	Repeated skin contact may cause dermatitis or an oil acne.		
Measures of Toxicity:	No test data available.		
Carcinogenic/Mutagen	ic Precautions: Non-carcinogenic and not expected to be mutagentic.		

12

ECOLOGICAL INFORMATION

**Ecological Precautions:** 

Avoid exposing to the environment.

**Ecological Effects:** 

No specific environmental or aquatic data available.

### 13 DISPOSAL CONSIDERATIONS

#### **Disposal Methods:**

Dispose of waste material in accordance with all local, state, and federal requirements.

**Disposal Containers:** 

Use properly approved container for disposal.



Lyden Oil Company

Page **7** of **7** –

### PROGUARD EC AW 46 Hydraulic Fluid

SDS Number: 17891

**Special Precautions:** 

Do not flush to surface waters or drains.

14	TRANSPORT INFORMATION		
UN Number:		Data not available	
UN Shipping Nar	<u>ne:</u>	Data not available	
Transport Hazar	d Class:	Data not available	
Packing Group:		Data not available	
Environmental H	lazards:		Data not available
Bulk Transport G	<u>Buidance:</u>		Data not available
Special Precaution	ons:		Not regulated by DOT.

### 15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

	16	OTHER INFORMATION
--	----	-------------------

Last Revision Date: 08/13/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.