

Lyden Oil Company

Page **1** of **8** –

1

2

## **PROGUARD Vintage DM3**

SDS Number: 17903

### PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD Vintage DM3
Revision Date:	09/19/2015
SDS Number:	17903
Common Name:	Solvent refined paraffinic oil
CAS Number:	Blend
Product Code:	17903
<u>Synonyms:</u>	Automatic transmission fluid, petroleum based lubricant

### **Company Identification:**

<i>Manufactured for:</i> LYDEN OIL COMPANY 3711 LeHarps Road Youngstown, OH 44515	
For Product Information:	1-330-792-1100
For Emergencies:	1-800-424-9300
CHEMTREC:	1-800-424-9300 or 1-703-527-3887

### HAZARDS IDENTIFICATION



Signal Word:

## DANGER

Hazard Classes/Categories:

Aspiration hazard, Category 1. Hazardous to the aquatic environment, Category chronic 3.



Lyden Oil Company

Page 2 of 8	
	PROGUARD Vintage DM3
SDS Number: 17903	
Hazard Statement(s):	
	H304: May be fatal if swallowed and enters airways.
	H412: Harmful to aquatic life with long-lasting effects.
Precaution Statement(s):	
	P101: If medical advice is needed, have product container or label at
	hand.
	P102: Keep out of reach of children.
	P103: Read label before use.
	P301+310: IF SWALLOWED: Immediately call a POISON
	CENTER/doctor.
	P331: Do NOT induce vomiting.
	P273: Avoid release to the environment.

Other Hazard Statement(s):

Repeated exposure may cause skin dryness or cracking.

3

COMPOSITION / INFORMATION ON INGREDIENTS

### Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	>90
Mineral Oil	Mixture	<5
Methacrylate copolymer	Proprietary	<2

\*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4 FIRST AID MEASURES
----------------------

### **Description of First Aid Measures:**

Inhalation:

If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.



Lyden Oil Company

Page <b>3</b> of <b>8</b>	
	PROGUARD Vintage DM3
SDS Number: 17903	
Skin Contact:	Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.
Eye Contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention.
Ingestion:	Rinse mouth with water. If symptoms develop, obtain medical attention.
Symptoms and Effects, both act	<u>ute and delayed:</u> No further relevent data available.
Recommended Actions:	Treat symptomatically. Call a doctor or poison control center for guidance.
5 FIRE FIGHTIN	IG MEASURES
Recommended Fire-Extinguishi	ng Equipment: Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.
Possible Hazards During a Fire:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Recommendations to Firefighte	ers: Proper protective equipment including breathing apparatus.



**PROGUARD Vintage DM3** 

Lyden Oil Company

SDS Number: 17903

Page 4 of 8 -

6 ACCIDENTAL RELEASE MEASU	RES
Personal Precautions:	
	Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition.
Emergency Procedures:	Contain spilled material, collect in suitable and properly labled containers.
Environmental Precautions:	Do not allow to reach sewage system or any water course.
	Do not allow to enter ground waters.
<u>Cleanup Procedures:</u>	Pick up excess with inert absorbant material. Treat contaminated absorbent same as spilled product.
7 HANDLING AND STORAGE	
Handling Precautions:	Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container.
<u>Storage Requirements:</u>	Keep container tightly sealed. Keep away from sources of ignition.
8 EXPOSURE CONTROLS / PERS	ONAL PROTECTION

## Exposure Limits:

-64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic (>90%):

ACGIH TLV – Long-term value: 5mg/m<sup>3</sup> OSHA PEL – Long-term value: 5mg/m<sup>3</sup>



Lyden Oil Company

Page **5** of **8** –

## **PROGUARD Vintage DM3**

SDS Number: 17903

**Engineering Controls:** 

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work. Use safety glasses and gloves.

#### 9

### PHYSICAL AND CHEMICAL PROPERTIES

Color:	Red
Physical State:	Liquid
Odor:	Data not available
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	-40°F
Boiling Point:	Data not available
Boiling Range:	Data not available
Flash Point:	204.4° C
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	0.872 (where water = 1)
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	7 mm <sup>2</sup> /sec (kinematic at 40° C)

### 10 STABILITY AND REACTIVITY

Stability:

Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.



Lyden Oil Company

Page <b>6</b> of <b>8</b> —		, , ,
C		PROGUARD Vintage DM3
SDS Number: 17	/903	
Conditions to Av	void:	
		Extreme temperature, sparks, open flame, and direct sunlight.
<u>Hazardous Reac</u>	tions:	
		No known hazardous reactions.
Incompatible M	aterials:	
		No further relevant information available.
<b>Decomposition</b>	Products:	
		Hazardous decomposition products are not expected to form.
11	TOXICOLOGICAL INFORMATIO	N
Routes of Expos	1110.	
noutes of Expos		Skin and eye contact are the primary routes of
		exposure although exposure may occur following

Exposure Effects:

Measures of Toxicity:

Carcinogenic/Mutagenic Precautions:

accidental ingestion.

Repeated skin contact may cause dermatitis or an oil acne.

No test data available.

Non-carcinogenic and not expected to be mutagentic.

#### 12

ECOLOGICAL INFORMATION

**Ecological Precautions:** 

Avoid exposing to the environment.



**PROGUARD Vintage DM3** 

Lyden Oil Company

SDS Number: 17903

Page 7 of 8 -

#### **Ecological Effects:**

No specific environmental or aquatic data available.

13	DISPOSAL CO	ONSIDERATIONS	
Disposal Method	<u>ds:</u>		Dispose of waste material in accordance with all local, state, and federal requirements.
Disposal Contair	<u>iers:</u>		Use properly approved container for disposal.
Special Precaution	ons:		Do not flush to surface waters or drains.
14	TRANSPORT	INFORMATION	
<u>UN Number:</u> <u>UN Shipping Nar</u> Transport Hazar Packing Group:		Data not available Data not available Data not available Data not available	
Environmental H	lazards:		Data not available
Bulk Transport G	<u>auidance:</u>		Data not available
Special Precaution	ons:		Not regulated by DOT.

## REGULATORY INFORMATION

15

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.



Lyden Oil Company

Page **8** of **8** —

## **PROGUARD Vintage DM3**

SDS Number: 17903

|--|

Last Revision Date: 09/19/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.