

Lyden Oil Company

Page **1** of **7** –

1

### **PROGUARD ND 60W Motor Oil**

SDS Number: 17927

#### PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD ND 60W Motor Oil
Revision Date:	08/19/2015
SDS Number:	17927
Common Name:	Petroleum, Heavy paraffinic oil
CAS Number:	Blend
Product Code:	17927
<u>Synonyms:</u>	Non-detergent monograde motor oil

#### **Company Identification:**

Manufactured for:LYDEN OIL COMPANY3711 LeHarps RoadYoungstown, OH 44515For Product Information:1-330-792-1100For Emergencies:1-800-424-9300CHEMTREC:1-800-424-9300 or 1-703-527-3887

#### 2 HAZARDS IDENTIFICATION

Signal Word:	None
Hazard Classes/Categories:	None
Hazard Statement(s):	None
Precaution Statement(s):	P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use.



Lyden Oil Company

Page 2 of 7 \_\_\_\_\_

### PROGUARD ND 60W Motor Oil

SDS Number: 17927

Other Hazard Statement(s):

Repeated exposure may cause skin dryness or cracking.

3	COMPOSITION / INFORMATION ON INGREDIENTS
---	--

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Residual oils, petroleum, solvent dewaxed	64742-62-7	80-90
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	10-20

\*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4	FIRST AID MEASURES

#### **Description of First Aid Measures:**

Inhalation:	If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.
Eye Contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention.
Ingestion:	Rinse mouth with water. If symptoms develop, obtain medical attention.

Symptoms and Effects, both acute and delayed:

No further relevent data available.



**PROGUARD ND 60W Motor Oil** 

Lyden Oil Company

SDS Number: 17927

Page **3** of **7** —

**Recommended Actions:** 

Treat symptomatically. Call a doctor or poison control center for guidance.

5 FIRE FIGHTING MEASURES	
Recommended Fire-Extinguishing Equipment:	
	Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.
Possible Hazards During a Fire:	
	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Recommendations to Firefighters:	No special measures required.
6 ACCIDENTAL RELEASE MEASU	RES
Personal Precautions:	Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition.
Emergency Procedures:	
	Contain spilled material, collect in suitable and properly labled containers.
Environmental Procedutions:	
	Do not allow to reach sewage system or any water course. Do not allow to enter ground waters.
6 ACCIDENTAL RELEASE MEASU   Personal Precautions:   Emergency Procedures:   Environmental Precautions:	Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition. Contain spilled material, collect in suitable and properly labled containers. Do not allow to reach sewage system or any wate course.



**PROGUARD ND 60W Motor Oil** 

Lyden Oil Company

SDS Number: 17927

Page 4 of 7 —

#### Cleanup Procedures:

Pick up excess with inert absorbant material.

### 7 HANDLING AND STORAGE Handling Precautions:

Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container.

Storage Requirements:

Keep container tightly sealed. Keep away from sources of ignition.

#### 8

#### EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Exposure Limits:**

-64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic (10-20%):

ACGIH TLV – Long-term value: 5mg/m<sup>3</sup> OSHA PEL – Long-term value: 5mg/m<sup>3</sup>

#### Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work. Use safety glasses and gloves.

#### 9

#### PHYSICAL AND CHEMICAL PROPERTIES

Color: Physical State: Odor: Odor Threshold: pH: Amber Liquid Data not available Data not available Data not available



**PROGUARD ND 60W Motor Oil** 

Lyden Oil Company

### SDS Number: 17927

Page 5 of 7 –

10

Melting Point:	Data not available
Boiling Point:	Data not available
Boiling Range:	Data not available
Flash Point:	204.4° C / 399.9° F (COC Method)
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	Data not available
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	17.5 mm <sup>2</sup> /sec (kinematic at 100° C)

#### STABILITY AND REACTIVITY

<u>Stability:</u>	Stable under normal conditions.
Reactivity:	Not reactive under normal conditions.
<u>Conditions to Avoid:</u>	Extreme temperature, sparks, open flame, and direct sunlight.
Hazardous Reactions:	No known hazardous reactions.
Incompatible Materials:	No further relevant information available.
Decomposition Products:	Hazardous decomposition products are not expected to form.



Lyden Oil Company

SDS Number: 17927

Page 6 of 7 -

### PROGUARD ND 60W Motor Oil

11 TOXICOLOGICAL INFORMATION	
Routes of Exposure:	
	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Exposure Effects:	
	Repeated skin contact may cause dermatitis or an oil acne.
Measures of Toxicity:	
	Component Acute Toxicity Estimates:
	Residual oils, petroleum, solvent dewaxed:
	Oral LD50: >5000 mg/kg (rat)
	Dermal LD50: >2000 mg/kg (rabbit)
	Inhalative LC50: 2.18 mg/l (4 hours) (rat)
Carcinogenic/Mutagenic Precautions:	
	Non-carcinogenic and not expected to be mutagentic.
12 ECOLOGICAL INFORMATION	

**Ecological Precautions:** 

Avoid exposing to the environment.

#### **Ecological Effects:**

No specific environmental or aquatic data available.

#### DISPOSAL CONSIDERATIONS

#### **Disposal Methods:**

13

Dispose of waste material in accordance with all local, state, and federal requirements.



Lyden Oil Company

Page **7** of **7** —

### PROGUARD ND 60W Motor Oil

SDS Number: 17927

**Disposal Containers:** 

Use properly approved container for disposal.

Special Precautions:

Do not flush to surface waters or drains.

#### 14 TRANSPORT INFORMATION

UN Number:Data not availableUN Shipping Name:Data not availableTransport Hazard Class:Data not availablePacking Group:Data not availableEnvironmental Hazards:Data not availableBulk Transport Guidance:Data not availableSpecial Precautions:Not regulated by DOT.

#### REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

#### 16 OTHER INFORMATION

Last Revision Date: 08/19/2015

15

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.