

Lyden Oil Company

Page **1** of **7** –

1

PROGUARD AW 220 Hydraulic Fluid

SDS Number: 17949

PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD AW 220 Hydraulic Fluid
Revision Date:	03/01/2016
SDS Number:	17949
Common Name:	Hydrotreated Heavy Paraffinic Oil
CAS Number:	Blend
Product Code:	17949
<u>Synonyms:</u>	Antiwear Hydraulic Fluid

Company Identification:

Manufactured for: LYDEN OIL COMPANY 3711 LeHarps Drive Youngstown, OH 44515

For Product Information:	1-330-792-1100
For Emergencies:	1-800-424-9300
CHEMTREC:	1-800-424-9300 or 1-703-527-3887

2 HAZARDS IDENTIFICATION

Signal Word:	None
Hazard Classes/Categories:	None
Hazard Statement(s):	None
Precaution Statement(s):	P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use.



Lyden Oil Company

Page 2 of 7 _____

PROGUARD AW 220 Hydraulic Fluid

SDS Number: 17949

Other Hazard Statement(s):

Repeated exposure may cause skin dryness or cracking.

3	COMPOSITION / INFORMATION ON INGREDIENTS	
---	--	--

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	>98
Additives	Proprietary	<2

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4	FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.
Eye Contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention.
Ingestion:	Rinse mouth with water. If symptoms develop, obtain medical attention.

Symptoms and Effects, both acute and delayed:

No further relevent data available.



PROGUARD AW 220 Hydraulic Fluid

Lyden Oil Company

SDS Number: 17949

Page **3** of **7** –

Recommended Actions:

Treat symptomatically. Call a doctor or poison control center for guidance.

5 FIRE FIGHTING MEASURES	
Recommended Fire-Extinguishing Equipment:	Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.
Possible Hazards During a Fire:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Recommendations to Firefighters:	Proper protective equipment including breathing apparatus.
6 ACCIDENTAL RELEASE MEASUR	RES
Personal Precautions:	Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition.
Emergency Procedures:	Contain spilled material, collect in suitable and properly labeled containers.
Environmental Precautions:	Do not allow to reach sewage system or any water course. Do not allow to enter ground waters.



Lyden Oil Company

Page 4 of 7 -

PROGUARD AW 220 Hydraulic Fluid

SDS Number: 17949

Cleanup Procedures:

Pick up excess with inert absorbant material.

7 HANDLING AND STORAGE Handling Precautions:

Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container.

Storage Requirements:

Keep container tightly sealed. Keep away from sources of ignition.

8

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

-64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic (>98%):

ACGIH TLV – Long-term value: 5mg/m³ OSHA PEL – Long-term value: 5mg/m³

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work. Use safety glasses and gloves.

9

PHYSICAL AND CHEMICAL PROPERTIES

Color: Physical State: Odor: Odor Threshold: pH: Amber Liquid Data not available Data not available Data not available



PROGUARD AW 220 Hydraulic Fluid

Lyden Oil Company

SDS Number: 17949

Page 5 of 7 –

10

Melting Point:	Data not available
Boiling Point:	>425° F
Boiling Range:	Data not available
Flash Point:	176.7° C / 350.1° F (TCC Method)
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	Data not available
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	220 mm ² /sec (kinematic at 40° C)

STABILITY AND REACTIVITY

<u>Stability:</u>	Stable under normal conditions.
Reactivity:	Not reactive under normal conditions.
<u>Conditions to Avoid:</u>	Extreme temperature, sparks, open flame, and direct sunlight.
Hazardous Reactions:	No known hazardous reactions.
Incompatible Materials:	No further relevant information available.
Decomposition Products:	Hazardous decomposition products are not expected to form.



PROGUARD AW 220 Hydraulic Fluid

Lyden Oil Company

SDS Number: 17949

Page 6 of 7 -

505 Nullibel: 17545	
11 TOXICOLOGICAL INFORMATION	N
Routes of Exposure:	Skin and eye contact are the primary routes of
	exposure although exposure may occur following accidental ingestion.
Exposure Effects:	
	Repeated skin contact may cause dermatitis or an oil acne.
Measures of Toxicity:	No. 1
	No test data available.
Carcinogenic/Mutagenic Precautions:	
	Non-carcinogenic and not expected to be mutagentic.
12 ECOLOGICAL INFORMATION	
12 ECOLOGICAL INFORMATION	
Ecological Precautions:	Avoid exposing to the environment.
Ecological Effects:	
No specific environmental	or aquatic data available.
13 DISPOSAL CONSIDERATIONS	
Disposal Methods:	
	Dispose of waste material in accordance with all
	local, state, and federal requirements.
Disposal Containers:	
	Use properly approved container for disposal.
Special Precautions:	
	Do not flush to surface waters or drains.



Lyden Oil Company

Page **7** of **7** –

PROGUARD AW 220 Hydraulic Fluid

SDS Number: 17949

14	TRANSPORT INFORMATION
<u>UN Number:</u>	Data not available
UN Shipping Na	me: Data not available
Transport Hazar	d Class: Data not available
Packing Group:	Data not available
Environmental H	Hazards: Data not available
Bulk Transport C	<u>Guidance:</u> Data not available
Special Precaution	ons: Not regulated by DOT.

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 OTHER INFORMATION	
----------------------	--

Last Revision Date: 03/01/2016

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.