

Lyden Oil Company

Page 1 of 7 –

1

2

PROGUARD ProCut 157 SC Metalworking Fluid

SDS Number: 17950

PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD ProCut 157 SC Metalworking Fluid
Revision Date:	08/18/2015
SDS Number:	17950
Common Name:	Hydrotreated Naphthenic Oil
CAS Number:	Blend
Product Code:	17950
<u>Synonyms:</u>	Petroleum based lubricant, Metalworking fluid

Company Identification:

<i>Manufactured for:</i> LYDEN OIL COMPANY 3711 LeHarps Road Youngstown, OH 44515	
For Product Information:	1-330-792-1100
For Emergencies:	1-800-424-9300
CHEMTREC:	1-800-424-9300 or 1-703-527-3887

HAZARDS IDENTIFICATION



Signal Word:

WARNING

Hazard Classes/Categories:

Skin irritant, Category 2. Hazardous to the aquatic environment, Category chronic 1.



Lyden Oil Company

Page 2 of 7	· · ·
	PROGUARD ProCut 157 SC Metalworking Fluid
SDS Number: 17950	
Hazard Statement(s):	
<u>·····································</u>	H315: Causes skin irritation.
	H410: Very toxic to aquatic life with long-lasting effects.
Precaution Statement(s):	
	P101: If medical advice is needed, have product container or label at
	hand.
	P102: Keep out of reach of children.
	P103: Read label before use.
	P264: Wash hands thoroughly after handling.

Other Hazard Statement(s):

Repeated exposure may cause skin dryness or cracking.

P302+352: IF ON SKIN: Wash with plenty of water.

P273: Avoid release to the environment.

COMPOSITION / INFORMATION ON INGREDIENTS 3

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	>80
Alkanes, Chloro, C14-C17	61788-76-9	<5
Non-hazardous Additives	N/A	10-20

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4	FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:

If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

Skin Contact:

Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.



Lyden Oil Company

Page 3 of 7	
	PROGUARD ProCut 157 SC Metalworking Fluid
SDS Number: 17950	
Eye Contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention.
Ingestion:	Rinse mouth with water. If symptoms develop, obtain medical attention.
Symptoms and Effects, both acu	i <u>te and delayed:</u> No further relevent data available.
Recommended Actions:	Treat symptomatically. Call a doctor or poison control center for guidance.
5 FIRE FIGHTING	G MEASURES
Recommended Fire-Extinguishin	ng Equipment: Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.
Possible Hazards During a Fire:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Recommendations to Firefighter	r <u>s:</u> No special measures required.
6 ACCIDENTAL	RELEASE MEASURES

Personal Precautions:

Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition.



Lyden Oil Company

Page 4 of 7	Lyden on company
Ū	PROGUARD ProCut 157 SC Metalworking Fluid
SDS Number: 17950	C
Emergency Procedures:	Contain spilled material, collect in suitable and properly labled containers.
Environmental Precautions:	Do not allow to reach sewage system or any water course. Do not allow to enter ground waters.
<u>Cleanup Procedures:</u>	Pick up excess with inert absorbant material.
7 HANDLING AND STORAGE	
Handling Precautions:	Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container.
Storage Requirements:	Keep container tightly sealed. Keep away from sources of ignition.
8 EXPOSURE CONTROLS / PERS	SONAL PROTECTION
Exposure Limits: No data available.	
Engineering Controls:	All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).
Personal Protective Equipment:	Wash hands before breaks and at the end of work. Use safety glasses and gloves.



Lyden Oil Company

SDS Number: 17950

Page 5 of 7 –

PROGUARD ProCut 157 SC Metalworking Fluid

9 PHYSICAL AND CHEMICAL PROPERTIES

Color:	Amber
Physical State:	Liquid
Odor:	Data not available
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	Data not available
Boiling Range:	Data not available
Flash Point:	180° C / 356° F (COC Method)
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	7.60 pounds per gallon at 60° F
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	315.6° C / 600.1° F
Decomposition Temperature:	Data not available
Viscosity:	Data not available

10	STABILITY AND REACTIVITY

<u>Stability:</u>	Stable under normal conditions.
<u>Reactivity:</u>	Not reactive under normal conditions.
<u>Conditions to Avoid:</u>	Extreme temperature, sparks, open flame, and direct sunlight.
Hazardous Reactions:	No known hazardous reactions.
Incompatible Materials:	No further relevant information available.



Lyden Oil Company

Page 6 of 7	, ,
-	PROGUARD ProCut 157 SC Metalworking Flui
SDS Number: 17950	
Decomposition Products:	Hazardous decomposition products are not expected to form.
11 TOXICOLOGICAL INFORM	ΛΑΤΙΟΝ
Routes of Exposure:	
	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Exposure Effects:	
	Repeated skin contact may cause dermatitis or an oil acne.
Measures of Toxicity:	
	No test data available.
Carcinogenic/Mutagenic Precautions:	Non-carcinogenic and not expected to be mutagentic.
12 ECOLOGICAL INFORMAT	ION
Ecological Precautions:	Avoid exposing to the environment.
Ecological Effects: No specific environment	mental or aquatic data available.
13 DISPOSAL CONSIDERATIO	ONS
Disposal Methods:	Dispose of waste material in accordance with all local, state, and federal requirements.
Disposal Containers:	Use properly approved container for disposal.



Lyden Oil Company

Page **7** of **7** –

PROGUARD ProCut 157 SC Metalworking Fluid

SDS Number: 17950

Special Precautions:

Do not flush to surface waters or drains.

14	TRANSPORT	INFORMATION	
<u>UN Number:</u>		Data not available	
UN Shipping Na	<u>me:</u>	Data not available	
Transport Hazar	d Class:	Data not available	
Packing Group:		Data not available	
Environmental Hazards:			
			Data not available
Bulk Transport Guidance:			
			Data not available
Special Dressuti	0000		
Special Precaution			Not regulated by DOT.

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16	OTHER INFORMATION

Last Revision Date: 08/18/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.