

Lyden Oil Company

Page 1 of 7 -

1

### **PROGUARD ProCut 185S Metalworking Fluid**

SDS Number: 17954

#### PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD ProCut 185S Metalworking Fluid
Revision Date:	11/20/2017
SDS Number:	17954
Common Name:	Hydrotreated heavy naphthenic oil
CAS Number:	Blend
Product Code:	17954
<u>Synonyms:</u>	Petroleum based lubricant, Metalworking fluid

#### **Company Identification:**

Manufactured for:<br/>LYDEN OIL COMPANY<br/>3711 LeHarps Drive<br/>Youngstown, OH 445151-330-792-1100<br/>1-800-424-9300For Product Information:<br/>For Emergencies:<br/>CHEMTREC:1-800-424-9300 or 1-703-527-3887

#### HAZARDS IDENTIFICATION



Signal Word:

2

Hazard Classes/Categories:

WARNING

Skin irritant, Category 2.

Hazard Statement(s):

H315: Causes skin irritation.



Lyden Oil Company

Page 2 of 7 —

### **PROGUARD ProCut 185S Metalworking Fluid**

SDS Number: 17954

#### Precaution Statement(s):

P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P103: Read label before use.
P302+352: IF ON SKIN: Wash with plenty of soap and water.

Other Hazard Statement(s):

Repeated exposure may cause skin dryness or cracking.

3 COMPOSITION / INFORMATION ON INGREDIENTS
--

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	<50
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	<50
Non-Hazardous Additives	N/A	<5

\*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4	FIRST AID MEASURES

#### **Description of First Aid Measures:**

Inhalation:	If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.
Eye Contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention.



# Safety Data Sheet

Lyden Oil Company

Page <b>3</b> of <b>7</b>	/
	PROGUARD ProCut 185S Metalworking Fluid
SDS Number: 17954	
Ingestion: Rinse mouth w attention.	vith water. If symptoms develop, obtain medical
Symptoms and Effects, both acute and delayed:	No further relevent data available.
Decommended Actions:	
Recommended Actions:	Treat symptomatically. Call a doctor or poison control center for guidance.
5 FIRE FIGHTING MEASURES	
Recommended Fire-Extinguishing Equipment:	Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.
Possible Hazards During a Fire:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Recommendations to Firefighters:	No special measures required.
6 ACCIDENTAL RELEASE MEASU	JRES
Personal Precautions:	Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition.
Emergency Procedures:	Contain spilled material, collect in suitable and properly labeled containers.



Page **4** of **7** —

# Safety Data Sheet

Lyden Oil Company

	PROGUARD ProCut 1855 Metalworking Fluid
SDS Number: 17954	
Environmental Precautions:	
	Do not allow to reach sewage system or any water course. Do not allow to enter ground waters.
Cleanup Procedures:	Pick up excess with inert absorbant material.
7 HANDLING AND ST	ORAGE
Handling Precautions:	
	Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container.
Storage Requirements:	Keep container tightly sealed.
	Keep away from sources of ignition.
8 EXPOSURE CONTRO	DLS / PERSONAL PROTECTION
Exposure Limits: No data availat	ole.
Engineering Controls:	All ventilation should be designed in accordance
	with OSHA standard (29 CFR 1910.94).
Personal Protective Equipment:	Wash hands before breaks and at the end of work.
	Use safety glasses and gloves.
9 PHYSICAL AND CHE	MICAL PROPERTIES
Color:	Amber

Color: Physical State: Odor: Amber Liquid Data not available



Lyden Oil Company

Page **5** of **7** –

### **PROGUARD ProCut 185S Metalworking Fluid**

#### SDS Number: 17954

Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	Data not available
Boiling Range:	Data not available
Flash Point:	180° C / 356° F (COC Method)
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	Data not available
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	Data not available

### 10 STABILITY AND REACTIVITY

<u>Stability:</u>	Stable under normal conditions.
Reactivity:	Not reactive under normal conditions.
<u>Conditions to Avoid:</u>	Extreme temperature, sparks, open flame, and direct sunlight.
Hazardous Reactions:	No known hazardous reactions.
Incompatible Materials:	No further relevant information available.
Decomposition Products:	Hazardous decomposition products are not expected to form.



**PROGUARD ProCut 185S Metalworking Fluid** 

Lyden Oil Company

SDS Number: 17954

Page 6 of 7 -

### 11 TOXICOLOGICAL INFORMATION Routes of Exposure: Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion. Exposure Effects: Repeated skin contact may cause dermatitis or an oil acne. Measures of Toxicity: No test data available. Carcinogenic/Mutagenic Precautions: Non-carcinogenic and not expected to be mutagentic. 12 **ECOLOGICAL INFORMATION Ecological Precautions:** Avoid exposing to the environment. **Ecological Effects:** No specific environmental or aquatic data available. 13 **DISPOSAL CONSIDERATIONS** Disposal Methods: Dispose of waste material in accordance with all local, state, and federal requirements. Disposal Containers: Use properly approved container for disposal. **Special Precautions:** Do not flush to surface waters or drains.



Lyden Oil Company

Page **7** of **7** –

### **PROGUARD ProCut 185S Metalworking Fluid**

SDS Number: 17954

14	TRANSPORT INFORMATION	
<u>UN Number:</u> UN Shipping Nar	Data not available ne: Data not available	
<u>Transport Hazar</u> Packing Group:		
Environmental F	lazards:	Data not available
<u>Bulk Transport G</u>		Data not available
Special Precaution		Not regulated by DOT.

#### 15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16	OTHER INFORMATION

Last Revision Date: 11/20/2017

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.