

Lyden Oil Company

Page **1** of **7** —

1

PROGUARD ProCut 123SP Metalworking Fluid

SDS Number: 17957

PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD ProCut 123SP Metalworking Fluid
Revision Date:	08/27/2015
SDS Number:	17957
Common Name:	Hydrotreated naphthenic oil
CAS Number:	Blend
Product Code:	17957
<u>Synonyms:</u>	Petroleum based lubricant, Metalworking fluid

Company Identification:

Manufactured for:
LYDEN OIL COMPANY
3711 LeHarps Road
Youngstown, OH 44515I-330-792-1100
1-800-424-9300For Product Information:
For Emergencies:
CHEMTREC:1-800-424-9300
1-800-424-9300 or 1-703-527-3887

HAZARDS IDENTIFICATION



Signal Word:

2

WARNING

Hazard Classes/Categories:

Skin irritant, Category 2.

Hazard Statement(s):

H315: Causes skin irritation.



Lyden Oil Company

Page **2** of **7** ——

PROGUARD ProCut 123SP Metalworking Fluid

SDS Number: 17957

Precaution Statement(s):

P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use. P302+352: IF ON SKIN: Wash with plenty of soap and water.

Other Hazard Statement(s):

Repeated exposure may cause skin dryness or cracking.

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Hydrotreated heavy naphthenic base oil	64741-52-5	>85
Fats and glyceridic oils	68990-81-8	<5
Non-hazardous components	N/A	<10

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4	FIRST AID MEASURES	
---	--------------------	--

Description of First Aid Measures:

Inhalation:	If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.
Eye Contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention.



Safety Data Sheet

Lyden Oil Company

Page 3 of 7 — Eyden On C	
	PROGUARD ProCut 123SP Metalworking Fluid
SDS Number: 17957	
Ingestion: Rinse mouth w attention.	vith water. If symptoms develop, obtain medical
Symptoms and Effects, both acute and delayed:	No further relevent data available.
Recommended Actions:	Treat symptomatically. Call a doctor or poison control center for guidance.
5 FIRE FIGHTING MEASURES	
Recommended Fire-Extinguishing Equipment:	Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.
Possible Hazards During a Fire:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Recommendations to Firefighters:	No special measures required.
6 ACCIDENTAL RELEASE MEASU	JRES
Personal Precautions:	Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition.
Emergency Procedures:	Contain spilled material, collect in suitable and properly labled containers.



Lyden Oil Company

Page 4 of 7	Lyden on company
	PROGUARD ProCut 123SP Metalworking Fluid
SDS Number: 17957	
Environmental Precautions:	
	Do not allow to reach sewage system or any water
	course.
	Do not allow to enter ground waters.
Cleanup Procedures:	
	Pick up excess with inert absorbant material.
7 HANDLING AN	ND STORAGE
Handling Precautions:	
	Handle with care and avoid spillage on the floor.
	Do not cut, weld, drill, grind, braze, or solder
	container.
Storage Requirements:	
	Keep container tightly sealed.
	Keep away from sources of ignition.
8 EXPOSURE CC	ONTROLS / PERSONAL PROTECTION
Evenesure Limiter	
<u>Exposure Limits:</u> No data a	available.
Engineering Controls:	
	All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).
Personal Protective Equipment:	
	Wash hands before breaks and at the end of work. Use safety glasses and gloves.
9 PHYSICAL ANI	D CHEMICAL PROPERTIES
Color:	Clear Dark

Color: Physical State: Odor: Clear Dark Liquid Sulfur



Lyden Oil Company

Page **5** of **7** –

PROGUARD ProCut 123SP Metalworking Fluid

Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	Data not available
Boiling Range:	Data not available
Flash Point:	162.8° C / 325.0° F (COC Method)
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	Data not available
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	30 mm ² /sec (kinematic at 40° C)

10 STABILITY AND REACTIVITY	
<u>Stability:</u>	Stable under normal conditions.
Reactivity:	Not reactive under normal conditions.
Conditions to Avoid:	Extreme temperature, sparks, open flame, and direct sunlight.
Hazardous Reactions:	No known hazardous reactions.
Incompatible Materials:	No further relevant information available.
Decomposition Products:	Hazardous decomposition products are not expected to form.



PROGUARD ProCut 123SP Metalworking Fluid

Lyden Oil Company

SDS Number: 17957

Page 6 of 7 —

11 TOXICOLOGICAL INFORMATION Routes of Exposure: Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion. **Exposure Effects:** Repeated skin contact may cause dermatitis or an oil acne. Measures of Toxicity: No test data available. Carcinogenic/Mutagenic Precautions: Non-carcinogenic and not expected to be mutagentic. 12 **ECOLOGICAL INFORMATION Ecological Precautions:** Avoid exposing to the environment. **Ecological Effects:** No specific environmental or aquatic data available. 13 DISPOSAL CONSIDERATIONS **Disposal Methods:** Dispose of waste material in accordance with all local, state, and federal requirements. Disposal Containers: Use properly approved container for disposal. **Special Precautions:** Do not flush to surface waters or drains.



Lyden Oil Company

Page 7 of 7 -

PROGUARD ProCut 123SP Metalworking Fluid

SDS	Number:	17957
505	Number.	1,22,

14	TRANSPORT INFORMATION	
<u>UN Number:</u>	Data not available	
UN Shipping Na	me: Data not available	
Transport Hazar	<u>d Class:</u> Data not available	
Packing Group:	Data not available	
Environmental	Hozarde:	
Environmental H	Data not available	
	Data not available	
Bulk Transport G	Guidance:	
	Data not available	
Special Precauti	ons:	
	Not regulated by DOT.	

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 OTHE	R INFORMATION

Last Revision Date: 08/27/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.