

Lyden Oil Company

Page **1** of **8** –

1

2

PROGUARD MG AW 22 Blue Hydraulic Fluid

SDS Number: 17974

PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD MG AW 22 Blue Hydraulic Fluid
Revision Date:	08/13/2015
SDS Number:	17974
Common Name:	Hydrotreated Heavy Paraffinic Oil
CAS Number:	Blend
Product Code:	17974
Synonyms:	Multi grade antiwear Hydraulic Fluid

Company Identification:

<i>Manufactured for:</i> LYDEN OIL COMPANY 3711 LeHarps Road Youngstown, OH 44515	
For Product Information:	1-330-792-1100
For Emergencies:	1-800-424-9300
CHEMTREC:	1-800-424-9300 or 1-703-527-3887

HAZARDS IDENTIFICATION



Signal Word:

WARNING

Hazard Classes/Categories:

Serious eye irritation, Category 2B. Skin irritant, Category 2.



Lyden Oil Company

Page 2 of 8	- <i>yaen en eempany</i>	
	PROGUARD MG AW 22 Blue Hydraulic Flui	
SDS Number: 17974	·	
Hazard Statement(s):		
<u>Hazara otatementtoji</u>	H320: Causes eye irritation.	
	H315: Causes skin irritation.	
Precaution Statement(s):		
	P101: If medical advice is needed, have product container or label at	
	hand.	
	P102: Keep out of reach of children.	
	P103: Read label before use.	
	P302+352: IF ON SKIN: Wash with plenty of water.	
	P305+351+338: IF IN EYES: Rinse cautiously with water for several	
	minutes. Remove contact lenses if present and easy to do – continue	
	rinsing.	
Other Hazard Statement(s):		

Repeated exposure may cause skin dryness or cracking.

3 COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	>95
Additives	Proprietary	<5

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4	FIRST AID MEASURES
---	--------------------

Description of First Aid Measures:

Inhalation:

No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.



Lyden Oil Company

age 3 of 8		
-	PROGUARD MG AW 22 Blue Hydraulic Flu	
SDS Number: 17974		
Skin Contact:		
	Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.	
Eye Contact:		
	Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention.	
Ingestion:	Dince mouth with water. If symptoms develop, obtain modical	
	Rinse mouth with water. If symptoms develop, obtain medical attention.	
Symptoms and Effects, both	acute and delayed:	
<u>- / </u>	No further relevent data available.	
Recommended Actions:		
	Treat symptomatically. Call a doctor or poison control center for guidance.	
5 FIRE FIGH	TING MEASURES	
Recommended Fire-Extingui	shing Equipment:	
<u>Necommended File-Extingu</u>	Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.	
Possible Hazards During a Fin	r <u>e:</u> Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.	
Recommendations to Firefig	<u>hters:</u> Proper protective equipment including breathing apparatus.	



PROGUARD MG AW 22 Blue Hydraulic Fluid

Lyden Oil Company

SDS Number: 17974

Page 4 of 8 -

6 ACCIDENTAL RELEASE MEASURES **Personal Precautions:** Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition. **Emergency Procedures:** Contain spilled material, collect in suitable and properly labled containers. **Environmental Precautions:** Do not allow to reach sewage system or any water course. Do not allow to enter ground waters. Cleanup Procedures: Pick up excess with inert absorbant material. HANDLING AND STORAGE 7 Handling Precautions: Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container. Storage Requirements: Keep container tightly sealed. Keep away from sources of ignition. **EXPOSURE CONTROLS / PERSONAL PROTECTION** 8 **Exposure Limits:** -64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic (>95%):

ACGIH TLV – Long-term value: 5mg/m³ OSHA PEL – Long-term value: 5mg/m³



Lyden Oil Company

Page 5 of 8 -

PROGUARD MG AW 22 Blue Hydraulic Fluid

SDS Number: 17974

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work. Use safety glasses and gloves.

9

PHYSICAL AND CHEMICAL PROPERTIES

Color:	Blue
Physical State:	Liquid
Odor:	Data not available
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	>425° F
Boiling Range:	Data not available
Flash Point:	248.9° C / 315.6° F (COC Method)
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	7.27 pounds per gallon at 60° F
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	22 mm ² /sec (kinematic at 40° C)

10 STABILITY AND REACTIVITY

Stability:

Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.



Lyden Oil Company

Page 6 of 8	
5	PROGUARD MG AW 22 Blue Hydraulic Fluid
SDS Number: 17974	•
<u>Conditions to Avoid:</u>	Extreme temperature, sparks, open flame, and direct sunlight.
Hazardous Reactions:	No known hazardous reactions.
Incompatible Materials:	No further relevant information available.
Decomposition Products:	Hazardous decomposition products are not expected to form.
11 TOXICOLOGICAL INFORMATIO	N
Routes of Exposure:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Exposure Effects:	Repeated skin contact may cause dermatitis or an

Measures of Toxicity:

Carcinogenic/Mutagenic Precautions:

Repeated skin contact may cause dermatitis or an oil acne.

No test data available.

Non-carcinogenic and not expected to be mutagentic.

12

ECOLOGICAL INFORMATION

Ecological Precautions:

Avoid exposing to the environment.

Ecological Effects:

No specific environmental or aquatic data available.



PROGUARD MG AW 22 Blue Hydraulic Fluid

Lyden Oil Company

SDS Number: 17974

Page 7 of 8 -

13 DISPOSAL	CONSIDERATIONS	
Disposal Methods:		Dispose of waste material in accordance with all local, state, and federal requirements.
Disposal Containers:		Use properly approved container for disposal.
Special Precautions:		Do not flush to surface waters or drains.
14 TRANSPORT INFORMATION		
<u>UN Number:</u> <u>UN Shipping Name:</u> <u>Transport Hazard Class:</u> <u>Packing Group:</u>	Data not available Data not available Data not available Data not available	
Environmental Hazards:		Data not available
Bulk Transport Guidance:		Data not available
Special Precautions:		Not regulated by DOT.
15 REGULATO	ORY INFORMATION	

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.



Lyden Oil Company

Page 8 of 8 -

PROGUARD MG AW 22 Blue Hydraulic Fluid

SDS Number: 17974

16

Last Revision Date: 08/13/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.