

Lyden Oil Company

Page **1** of **8** –

1

PROGUARD Syn Blend 10W-30 Motor Oil

SDS Number: 17986

PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD Syn Blend 10W-30 Motor Oil
Revision Date:	06/24/2016
SDS Number:	17986
Common Name:	Heavy paraffinic oil/Synthetic base oil
CAS Number:	Blend
Product Code:	17986
<u>Synonyms:</u>	Passenger car motor oil

Company Identification:

<i>Manufactured for:</i> LYDEN OIL COMPANY 3711 LeHarps Road Youngstown, OH 44515	
For Product Information:	1-330-792-1100
For Emergencies:	1-800-424-9300
CHEMTREC:	1-800-424-9300 or 1-703-527-3887

2 HAZARDS IDENTIFICATION

Signal Word:	None
Hazard Classes/Categories:	Hazardous to the aquatic environment, Category chronic 3.
Hazard Statement(s):	H412: Harmful to aquatic life with long-lasting effects.
<u>Precaution Statement(s):</u>	P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use. P273: Avoid release to the environment.



Lyden Oil Company

Page 2 of 8 -

PROGUARD Syn Blend 10W-30 Motor Oil

SDS Number: 17986

Other Hazard Statement(s):

Repeated exposure may cause skin dryness or cracking.

3	COMPOSITION / INFORMATION ON INGREDIENTS	
---	--	--

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	80-90
Additives	N/A	<15
Zinc Alkyldithiophosphate	68649-42-3	<5

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

	4	FIRST AID MEASURES
--	---	--------------------

Description of First Aid Measures:

Inhalation:	If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.
Eye Contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult medical attention.
Ingestion:	Rinse mouth with water. If symptoms develop, obtain medical attention.



Lyden Oil Company

SDS Number: 17986

Page **3** of **8** –

PROGUARD Syn Blend 10W-30 Motor Oil

556 Hambert 17566	
Symptoms and Effects, both acute and delayed:	No further relevent data available.
Recommended Actions:	Treat symptomatically. Call a doctor or poison control center for guidance.
5 FIRE FIGHTING MEASURES	
<u>Recommended Fire-Extinguishing Equipment:</u>	Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.
Possible Hazards During a Fire:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
<u>Recommendations to Firefighters:</u>	No special measures required.
6 ACCIDENTAL RELEASE MEASUR	RES
Personal Precautions:	Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition.
Emergency Procedures:	Contain spilled material, collect in suitable and properly labled containers.



Page **4** of **8** –

Safety Data Sheet

Lyden Oil Company

		PROGUARD Syn Blend 10W-3	80 Motor Oil
SDS Number: 17986			
Environmental Precaut	tions:		
		Do not allow to reach sewage system or any water course.	
		Do not allow to enter ground waters.	
Cleanup Procedures:			
		Pick up excess with inert absorbant material.	
7 HAN	DLING AND STORAGE]
Handling Precautions:			
<u></u>		Handle with care and avoid spillage on the floor.	
		Do not cut, weld, drill, grind, braze, or solder container.	
Storage Requirements	<u>:</u>	<i>v</i>	
		Keep container tightly sealed. Keep away from sources of ignition.	
8 EXPC	SURE CONTROLS / PERSO	NAL PROTECTION	
Exposure Limits:	64742 CE O Distillatos (nat	relevent deversed because peroffinic (20,000/)	
	-64742-65-0 Distillates (per	roleum), solvent-dewaxed heavy paraffinic (80-90%):	
	ACGIH TLV – Long-term valu OSHA PEL – Long-term valu		
Engineering Controls:			
		All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).	
Personal Protective Eq	uipment:		
		Wash hands before breaks and at the end of work. Use safety glasses and gloves.	



Lyden Oil Company

SDS Number: 17986

Page 5 of 8 -

9

PROGUARD Syn Blend 10W-30 Motor Oil

Color:	Amber
Physical State:	Liquid
Odor:	Data not available
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	Data not available
Boiling Range:	Data not available
Flash Point:	176.7° C / 350.1° F (COC Method)
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	7.33 pounds per gallon at 60° F
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	10.5 mm ² /sec (kinematic at 100° C)

PHYSICAL AND CHEMICAL PROPERTIES

10	STABILITY AND REACTIVITY	
<u>Stability:</u>		
	S	table under normal conditions.
Reactivity:		
-	Ν	Not reactive under normal conditions.
Conditions to Av	void:	
	E	extreme temperature, sparks, open flame, and lirect sunlight.
Hazardous Reac	tions:	

No known hazardous reactions.



Lyden Oil Company

Page 6 of 8	
0	PROGUARD Syn Blend 10W-30 Motor Oil
SDS Number: 17986	-
Incompatible Materials:	
	No further relevant information available.
Decomposition Products:	
	Hazardous decomposition products are not expected to form.
11 TOXICOLOGICAL IN	FORMATION
Routes of Exposure:	Skin and eye contact are the primary routes of
	exposure although exposure may occur following accidental ingestion.
Exposure Effects:	
	Repeated skin contact may cause dermatitis or an oil acne.
Measures of Toxicity:	
	No test data available.
Carcinogenic/Mutagenic Precautions:	
	Non-carcinogenic and not expected to be mutagentic.
12 ECOLOGICAL INFOR	MATION
Ecological Precautions:	
	Avoid exposing to the environment.
Ecological Effects:	
No specific en	vironmental or aquatic data available.



PROGUARD Syn Blend 10W-30 Motor Oil

Lyden Oil Company

SDS Number: 17986

Page 7 of 8 -

13	DISPOSAL CO	NSIDERATIONS	
Disposal Method	<u>ls:</u>		Dispose of waste material in accordance with all local, state, and federal requirements.
<u>Disposal Contain</u>	<u>ers:</u>		Use properly approved container for disposal.
Special Precautic	ons:		Do not flush to surface waters or drains.
14	TRANSPORT I	NFORMATION	
<u>UN Number:</u> <u>UN Shipping Nan</u> <u>Transport Hazaro</u> <u>Packing Group:</u>	<u>ne:</u> d Class:	Data not available Data not available Data not available Data not available	
Environmental H	lazards:		Data not available
Bulk Transport G	iuidance:		Data not available
Special Precautic	ons:		Not regulated by DOT.
15			

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

SARA Section 313: Contains <1% Zn



Lyden Oil Company

Page 8 of 8 -

PROGUARD Syn Blend 10W-30 Motor Oil

SDS Number: 17986

16 OTHER INFORMATION	16 OTHER
----------------------	----------

Last Revision Date: 06/24/2016

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.