

Lyden Oil Company

Page **1** of **8** –

1

2

PROGUARD Mercon V

SDS Number: 203011

PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD Mercon V
Revision Date:	03/01/2016
SDS Number:	203011
Common Name:	Hydrotreated Paraffinic Oil
CAS Number:	Blend
Product Code:	203011
<u>Synonyms:</u>	Automatic Transmission Fluid
Power Steering Fluid	

Company Identification:

Manufactured for: LYDEN OIL COMPANY 3711 LeHarps Drive Youngstown, OH 44515

For Product Information:	1-330-792-1100
For Emergencies:	1-800-424-9300
CHEMTREC:	1-800-424-9300 or 1-703-527-3887

HAZARDS IDENTIFICATION

Signal Word:	None
Hazard Classes/Categories:	None
Hazard Statement(s):	None
Precaution Statement(s):	P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use.



Lyden Oil Company

Page 2 of 8 -

PROGUARD Mercon V

SDS Number: 203011

Other Hazard Statement(s):

-NFPA Ratings: Health = 0 Fire = 1 Reactivity = 0

3

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates, petroleum, hydrotreated light paraffinic	64742-55-8	>40
Distillates, petroleum, hydrotreated heavy paraffinic	64742-54-7	>35

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4 FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:

	First aid is not normally required. If breathing difficulties develop, move victim away from source of exposure and into fresh air in a position comfortable for breathing. Seek immediate medical attention.
Skin Contact:	
	Remove contaminated shoes and clothing and cleanse affected
	area(s) thoroughly by washing with mild soap and water or a waterless hand cleaner. If irritation or redness develops and persists,
	seek medical attention.
Eye Contact:	
	If irritation or redness develops from exposure, flush eyes with clean
	water. If symptoms persist, seek medical attention.



Page **3** of **8** —

Safety Data Sheet

Lyden Oil Company

	PROGUARD Mercon V
SDS Number: 203011	
	normally required; however, if swallowed and elop, seek medical attention.
Symptoms and Effects, both acute and delayed:	Inhalation of oil mists or vapors generated at elevated temperatures may cause respiratory irritation. Accidental ingestion can result in minor irritation of the digestive tract, nausea and diarrhea. Dry skin and possible irritation with repeated or prolonged exposure.
Recommended Actions:	Treat symptomatically. Call a doctor or poison control center for guidance.
5 FIRE FIGHTING MEASURES	
<u>Recommended Fire-Extinguishing Equipment:</u>	Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.
Possible Hazards During a Fire:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Recommendations to Firefighters:	Proper protective equipment including breathing apparatus.



Lyden Oil Company

PROGUARD Mercon V

SDS Number: 203011

Page 4 of 8 -

6 ACCIDENTAL RELEASE MEASURES **Personal Precautions:** Personal precautions, protective equipment and emergency procedures: This material may burn, but will not ignite readily. Keep all sources of ignition away from spill/release. Stay upwind and away from spill/release. Avoid direct contact with material. For large spillages, notify persons down wind of the spill/release, isolate immediate hazard area and keep unauthorized personnel out. Wear appropriate protective equipment, including respiratory protection, as conditions warrant. **Emergency Procedures:** Contain spilled material, collect in suitable and properly labeled containers. **Environmental Precautions:** Do not allow to reach sewage system or any water course. Do not allow to enter ground waters. **Cleanup Procedures:** Pick up excess with inert absorbant material. HANDLING AND STORAGE 7 Handling Precautions: Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container. Storage Requirements: Keep container tightly sealed. Keep away from sources of ignition.



Lyden Oil Company

Page **5** of **8** —

PROGUARD Mercon V

SDS Number: 203011

8	EXPOSURE CONTROLS / PERSONAL PROTECTION
Exposure Limits:	
	-64742-54-7 Distillates (petroleum), hydrotreated heavy naphthenic (>35%):
	ACGIH TLV – Short-term value: 10mg/m ³

Long-term value: 5mg/m³ OSHA PEL – Long-term value: 5mg/m³

-64742-55-8 Distillates (petroleum), hydrotreated light naphthenic (>40%):

ACGIH TLV – Short-term value: 10mg/m³ Long-term value: 5mg/m³ OSHA PEL – Long-term value: 5mg/m³

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work. Use safety glasses and gloves.

9

PHYSICAL AND CHEMICAL PROPERTIES

Color:	Red
Physical State:	Liquid
Odor:	Petroleum
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	Data not available
Boiling Range:	Data not available
Flash Point:	157° C / 315° F (PMCC Method)
Evaporation Rate:	<1
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	<1 mmHg at 20° C
Vapor Density:	>1



Lyden Oil Company

PROGUARD Mercon V

SDS Number: 203011

Page 6 of 8 -

0.85 (7.08 pounds/gal)
Insoluble in water
Data not available
Data not available
Data not available
7.2-8.1 mm ² /sec (kinem

10 STABILITY AND REACTIVITY	
<u>Stability:</u>	
	Stable under normal conditions.
<u>Reactivity:</u>	
	Not reactive under normal conditions.
Conditions to Avoid:	
	Extreme temperature, sparks, open flame, and direct sunlight.
Hazardous Reactions:	No known hazardous reactions.
	No known nazarubus reactions.
Incompatible Materials:	
	Strong oxidizers and strong reducing agents.
Decomposition Products:	
	Oxides of carbon and hydrogen.
11 TOXICOLOGICAL INFORMATIO	N
Routes of Exposure:	Skin and eye contact are the primary routes of
	exposure although exposure may occur following
	accidental ingestion.
Exposure Effects:	
	Repeated skin contact may cause dermatitis or an oil acne.
	on acric.

inematic at 40° C)



Lyden Oil Company

PROGUARD Mercon V

SDS Number: 203011

Page 7 of 8 -

Measures of Toxicity:

ATE (Acute Toxicity Estimates):

Oral LD50: >5000 mg/kg Dermal LD50: >2000 mg/kg Inhalative LC50/4 h: >5000 mg/l

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be mutagentic.

12 ECOLOGICAL INFORMATION

Ecological Precautions:

Avoid exposing to the environment.

Ecological Effects:

14

No specific environmental or aquatic data available.

13	DISPOSAL CONSIDERATIONS	
Disposal Method	<u>ds:</u>	Dispose of waste material in accordance with all local, state, and federal requirements.
<u>Disposal Contair</u>	<u>ners:</u>	Use properly approved container for disposal.
<u>Special Precauti</u>	<u>ons:</u>	Do not flush to surface waters or drains.

TRANSPORT INFORMATION

UN Number:Data not availableUN Shipping Name:Data not availableTransport Hazard Class:Data not availablePacking Group:Data not available



Lyden Oil Company

PROGUARD Mercon V

SDS Number: 203011

Page 8 of 8 -

Environmental Hazards:

Bulk Transport Guidance:

Data not available

Data not available

Special Precautions:

Not regulated by DOT.

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16	OTHER INFORMATION
----	-------------------

Last Revision Date: 03/01/2016

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.