

Lyden Oil Company

Page **1** of **7** —

## **PROGUARD Lithium Complex Block Grease**

SDS Number: 610616

#### PRODUCT AND COMPANY INFORMATION

Product Name: PROGUARD Lithium Complex Block Grease

<u>Revision Date:</u> 08/10/2015 <u>SDS Number:</u> 610616

<u>Common Name:</u> Lithium Complex Block Grease

<u>CAS Number:</u> Blend <u>Product Code:</u> 1049

Synonyms: Lithium Complex Block Grease

#### **Company Identification:**

Manufactured for: LYDEN OIL COMPANY 3711 LeHarps Road Youngstown, OH 44515

For Product Information: 1-330-792-1100 For Emergencies: 1-800-424-9300

CHEMTREC: 1-800-424-9300 or 1-703-527-3887

2 HAZARDS IDENTIFICATION

Signal Word: None

Hazard Classes/Categories:

None

Hazard Statement(s):

None

Precaution Statement(s):

P101: If medical advice is needed, have product container or label at

hand.

P102: Keep out of reach of children.

P103: Read label before use.



Lyden Oil Company

Page 2 of 7 -

## **PROGUARD Lithium Complex Block Grease**

SDS Number: 610616

Other Hazard Statement(s):

-NFPA Ratings: Health = 0 Fire = 1 Reactivity = 0

3

## **COMPOSITION / INFORMATION ON INGREDIENTS**

#### **Ingredients:**

Mixture of the substances listed below with nonhazardous additions.

| Chemical Name                                          | CAS Number | Percentage |
|--------------------------------------------------------|------------|------------|
| Residual oils (petroleum), solvent-refined             | 64742-01-4 | 50-100     |
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 | 10-<25     |

<sup>\*</sup>Any concentration shown as a range is to protect confidentiality or is due to batch variation.

#### FIRST AID MEASURES

#### **Description of First Aid Measures:**

Inhalation:

No treatment necessary under normal conditions of use. If

symptoms persist, obtain medical advice.

Skin Contact:

Generally the product does not irritate the skin.

Eye Contact:

Rinse opened eye for several minutes under running water. If

symptoms persist, consult medical attention.

Ingestion:

Rinse mouth with water. If symptoms develop, obtain medical

attention.



Lyden Oil Company

Page **3** of **7** —

## **PROGUARD Lithium Complex Block Grease**

SDS Number: 610616

Symptoms and Effects, both acute and delayed:

No further relevent data available.

**Recommended Actions:** 

Treat symptomatically. Call a doctor or poison

control center for guidance.

5 FIRE FIGHTING MEASURES

Recommended Fire-Extinguishing Equipment:

Use fire-fighting measures and equipment suitable

for the environment.

Possible Hazards During a Fire:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Recommendations to Firefighters:

No special measures required.

6 ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** 

Avoid contact with skin and eyes.

**Emergency Procedures:** 

Contain spilled material, collect in suitable and

properly labeled containers.

**Environmental Precautions:** 

Do not allow to reach sewage system or any water

course.

Do not allow to enter ground waters.



Lyden Oil Company

Page **4** of **7** —

## **PROGUARD Lithium Complex Block Grease**

SDS Number: 610616

Cleanup Procedures:

Pick-up mechanically.

7 HANDLING AND STORAGE

**Handling Precautions:** 

No special precautions needed if used correctly.

**Storage Requirements:** 

Keep container tightly sealed.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Limits:** 

-64742-01-4 Residual oils (petroleum), solvent-refined (50-100%):

OSHA PEL - Long-term value: 5mg/m3

-64742-52-5 Distillates (petroleum), hydrotreated heavy naphthenic (10-<25%):

ACGIH TLV - Short-term value: 10mg/m<sup>3</sup>

Long-term value: 5mg/m<sup>3</sup>

OSHA PEL – Long-term value: 5mg/m³

**Engineering Controls:** 

All ventilation should be designed in accordance

with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work.

Use gloves.

PHYSICAL AND CHEMICAL PROPERTIES

Color: Amber Physical State: Solid

Odor: Petroleum-like



Lyden Oil Company

Page **5** of **7** —

## **PROGUARD Lithium Complex Block Grease**

SDS Number: 610616

Odor Threshold: Data not available Data not available pH: Data not available **Melting Point:** 338° C / 640° F **Boiling Point:** Data not available **Boiling Range:** Flash Point: 266° C / 511° F **Evaporation Rate:** Data not available Flammability: Data not available Flammability Limits: Data not available Vapor Pressure: Data not available Vapor Density: Data not available

Relative Density: 7.700 pounds per gallon at 68° F

Solubilities: Insoluble in water
Partition Coefficient: Data not available
Auto-Ignition Temperature: Data not available
Decomposition Temperature: Data not available
Viscosity: Data not available

#### 10 STABILITY AND REACTIVITY

Stability:

Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.

Conditions to Avoid:

No further relevant information available.

**Hazardous Reactions:** 

No known hazardous reactions.

Incompatible Materials:

No further relevant information available.

**Decomposition Products:** 

Hazardous decomposition products are not

expected to form.



Lyden Oil Company

Page **6** of **7** —

## **PROGUARD Lithium Complex Block Grease**

SDS Number: 610616

11 TOXICOLOGICAL INFORMATION

Routes of Exposure:

Skin and eye contact are the primary routes of

exposure although exposure may occur following

accidental ingestion.

Exposure Effects:

No known irritating or sensitizing effects.

Measures of Toxicity:

Acute Toxicity Estimates:

Oral LD50: 3577 mg/kg (rat)

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be

mutagentic.

12 ECOLOGICAL INFORMATION

**Ecological Precautions:** 

Avoid exposing to the environment.

**Ecological Effects:** 

Water hazard class 1 (self-assessment): Slightly hazardous to water.

13 DISPOSAL CONSIDERATIONS

Dispose of waste material in accordance with all

local, state, and federal requirements.

**Disposal Containers:** 

Disposal Methods:

Use properly approved container for disposal.



Lyden Oil Company

Page **7** of **7** —

## **PROGUARD Lithium Complex Block Grease**

SDS Number: 610616

**Special Precautions:** 

Small quantities can be disposed of with household

garbage.

Do not flush to surface waters or drains.

### 14 TRANSPORT INFORMATION

UN Number:Data not availableUN Shipping Name:Data not availableTransport Hazard Class:Data not availablePacking Group:Data not available

**Environmental Hazards:** 

Data not available

**Bulk Transport Guidance:** 

Data not available

**Special Precautions:** 

Not regulated by DOT.

#### 15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

## 16 OTHER INFORMATION

Last Revision Date: 08/10/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.