

Lyden Oil Company

Page **1** of **8** —

PROGUARD Cotton Picker Grease

SDS Number: 611474-00

PRODUCT AND COMPANY INFORMATION

Product Name: PROGUARD Cotton Picker Grease

Revision Date: 08/05/2015 SDS Number: 611474-00

<u>Common Name:</u> PROGUARD Cotton Picker Grease

<u>CAS Number:</u> Blend <u>Product Code:</u> 1063

Synonyms: Cotton Picker Grease

Company Identification:

Manufactured for: LYDEN OIL COMPANY 3711 LeHarps Road Youngstown, OH 44515

For Product Information: 1-330-792-1100 For Emergencies: 1-800-424-9300

CHEMTREC: 1-800-424-9300 or 1-703-527-3887

HAZARDS IDENTIFICATION



Signal Word: DANGER

Hazard Classes/Categories:

Aspiration hazard, Category 1.

Hazard Statement(s):

H304: May be fatal if swallowed and enters airways.



Lyden Oil Company

Page 2 of 8 -

PROGUARD Cotton Picker Grease

SDS Number: 611474-00

Precaution Statement(s):

P101: If medical advice is needed, have product container or label at

hand.

P102: Keep out of reach of children.

P103: Read label before use.

P301+310: IF SWALLOWED: Immediately call a POISON

CENTER/doctor

P331: Do NOT induce vomiting.

P405: Store locked up.

P501: Dispose of contents/container in accordance with

local/regional/national/international regulation.

Other Hazard Statement(s):

-NFPA Ratings:

Health = 0

Fire = 1

Reactivity = 0

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	50-100

^{*}Any concentration shown as a range is to protect confidentiality or is due to batch variation.

FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:

If symptoms develop, move victim to fresh air. If symptoms persist,

obtain medical attention.



Lyden Oil Company

Page **3** of **8** —

PROGUARD Cotton Picker Grease

SDS Number: 611474-00

Skin Contact:

Generally the product does not irritate the skin.

Eye Contact:

Rinse opened eye for several minutes under running water. If

symptoms persist, consult medical attention.

Ingestion:

Rinse mouth with water. If symptoms develop, obtain medical

attention.

Symptoms and Effects, both acute and delayed:

No further relevent data available.

Recommended Actions:

Treat symptomatically. Call a doctor or poison

control center for guidance.

5 FIRE FIGHTING MEASURES

Recommended Fire-Extinguishing Equipment:

Use fire-fighting measures and equipment suitable

for the environment.

Possible Hazards During a Fire:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Recommendations to Firefighters:

No special measures required.



Lyden Oil Company

Page 4 of 8 -

PROGUARD Cotton Picker Grease

SDS Number: 611474-00

ACCIDENTAL RELEASE MEASURES

Personal Precautions:

None Required.

Emergency Procedures:

Contain spilled material, collect in suitable and

properly labeled containers.

Environmental Precautions:

Do not allow to reach sewage system or any water

course.

Do not allow to enter ground waters.

Cleanup Procedures:

Absorb with liquid-binding material (sand,

diatomite, acid binders, iniversal binders, sawdust.

7 HANDLING AND STORAGE

Handling Precautions:

No special precautions needed if used correctly.

Storage Requirements:

Keep container tightly sealed.

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

-64742-53-6 Distillates (petroleum), hydrotreated light naphthenic (50-100%):

ACGIH TLV - Short-term value: 10 mg/m³

Long-term value: 5 mg/m³

NIOSH REL - Short-term value: 10 mg/m³

Long-term value: 5 mg/m³

OSHA PEL - Long-term value: 5 mg/m³



Lyden Oil Company

Page 5 of 8 -

PROGUARD Cotton Picker Grease

SDS Number: 611474-00

-64742-52-5 Distillates (petroleum), hydrotreated heavy naphthenic (10-<25%):

ACGIH TLV - Short-term value: 10mg/m3

Long-term value: 5mg/m³

OSHA PEL – Long-term value: 5mg/m³

Engineering Controls:

All ventilation should be designed in accordance

with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin. Use safety glasses and gloves.

9 PHYSICAL AND CHEMICAL PROPERTIES

Color: Light amber **Physical State:** Semi-solid Odor: Petroleum-like Odor Threshold: Data not available pH: Data not available **Melting Point:** Data not available **Boiling Point:** 225° C / 437° F Boiling Range: Data not available Flash Point: 147° C / 297° F **Evaporation Rate:** Data not available Data not available Flammability: Flammability Limits: Data not available Vapor Pressure: Data not available Vapor Density: Data not available

Relative Density: 7.51 pounds per gallon at 68° F

Solubilities: Insoluble in water
Partition Coefficient: Data not available
Auto-Ignition Temperature: Data not available
Decomposition Temperature: Data not available
Viscosity: Data not available



Lyden Oil Company

Page **6** of **8** —

PROGUARD Cotton Picker Grease

SDS Number: 611474-00

10	STABILITY AND REACTIVITY
Stability:	Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.

Conditions to Avoid:

No further relevant information available.

Hazardous Reactions:

No known hazardous reactions.

Incompatible Materials:

No further relevant information available.

Decomposition Products:

Hazardous decomposition products are not

expected to form.

11 TOXICOLOGICAL INFORMATION

Routes of Exposure:

Skin and eye contact are the primary routes of exposure although exposure may occur following

accidental ingestion.

Exposure Effects:

No known irritating or sensitizing effects.

Measures of Toxicity:

Acute Toxicity Estimates:

Oral LD50: 39683 mg/kg (rat)

<u>Carcinogenic/Mutagenic Precautions:</u>

Non-carcinogenic and not expected to be

mutagentic.



Lyden Oil Company

Page **7** of **8** —

PROGUARD Cotton Picker Grease

SDS Number: 611474-00

12 ECOLOGICAL INFORMATION

Ecological Precautions:

Avoid exposing to the environment.

Ecological Effects:

Water hazard class 1 (self-assessment): Slightly hazardous to water.

13 DISPOSAL CONSIDERATIONS

Dispose of waste material in accordance with all

local, state, and federal requirements.

Disposal Containers:

Disposal Methods:

Use properly approved container for disposal.

Special Precautions:

Do not dispose of with household garbage. Do not flush to surface waters or drains.

14 TRANSPORT INFORMATION

UN Number:Data not availableUN Shipping Name:Data not availableTransport Hazard Class:Data not availablePacking Group:Data not available

Environmental Hazards:

Data not available

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.



Lyden Oil Company

Page 8 of 8 -

PROGUARD Cotton Picker Grease

SDS Number: 611474-00

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 OTHER INFORMATION

Last Revision Date: 08/05/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.