

Lyden Oil Company

Page 1 of 8 -

PROGUARD Synthetic CD 50W Gear Oil

SDS Number: 702051

PRODUCT AND COMPANY INFORMATION

Product Name: PROGUARD Synthetic CD 50W Gear Oil

 Revision Date:
 02/05/2016

 SDS Number:
 702051

<u>Common Name:</u> Automotive gear oil

<u>CAS Number:</u> Blend <u>Product Code:</u> 702051

Synonyms: Synthetic gear oil

Company Identification:

Manufactured for: LYDEN OIL COMPANY 3711 LeHarps Drive Youngstown, OH 44515

For Product Information: 1-330-792-1100 For Emergencies: 1-800-424-9300

CHEMTREC: 1-800-424-9300 or 1-703-527-3887

2 HAZARDS IDENTIFICATION



Signal Word: WARNING

Hazard Classes/Categories:

Serious eye irritation, Category 2A. Hazardous to the aquatic environment, Category chronic 4.



Lyden Oil Company

Page 2 of 8 -

PROGUARD Synthetic CD 50W Gear Oil

SDS Number: 702051

<u>Hazard Statement(s):</u>

H319: Causes serious eye irritation.

H413: May cause long lasting effects to aquatic life.

Precaution Statement(s):

P101: If medical advice is needed, have product container or label at

hand.

P102: Keep out of reach of children.

P103: Read label before use.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue

rinsing.

P273: Avoid release to the environment.

Other Hazard Statement(s):

-NFPA Ratings:

Health = 1 Fire = 1

Reactivity = 0

Repeated exposure may cause skin dryness or cracking.

2

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Synthetic base oil	Proprietary	50-60
Polybutene	9003-29-6	<10
Mineral oil	Proprietary	10-20
Diisodecyl adipate	27178-16-1	5-10
Alkyl adipate	Proprietary	0.1-0.3
Alkoxylated long chain alkyl amine	Proprietary	0.1-0.3
Phosphorus acid salt	Proprietary	0.1-0.3
Alkyl alkoxy amine	Proprietary	0.0-0.1
Long chain alkyl dithio thiadiazole	Proprietary	0.0-0.1
Poly long chain alkyl methacrylate	Proprietary	1-5
Alkyl methacrylate	Proprietary	



Lyden Oil Company

Page 3 of 8 -

PROGUARD Synthetic CD 50W Gear Oil

SDS Number: 702051

4 FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:

If symptoms develop, move victim to fresh air. If symptoms persist,

obtain medical attention.

Skin Contact:

Wash with soap and water. Remove contaminated clothing and wash

before reuse. Get medical attention if needed.

Eye Contact:

Rinse opened eye for several minutes under running water. If

symptoms persist, consult medical attention.

Ingestion:

Rinse mouth with water. If symptoms develop, obtain medical

attention.

Symptoms and Effects, both acute and delayed:

No further relevent data available.

Recommended Actions:

Treat symptomatically. Call a doctor or poison

control center for guidance.

FIRE FIGHTING MEASURES

Recommended Fire-Extinguishing Equipment:

Dry chemical, carbon dioxide, foam, or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F/100°C. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces.

^{*}Any concentration shown as a range is to protect confidentiality or is due to batch variation.



Lyden Oil Company

Page **4** of **8** —

PROGUARD Synthetic CD 50W Gear Oil

SDS Number: 702051

Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

Possible Hazards During a Fire:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Recommendations to Firefighters:

Proper protective equipment including breathing

apparatus.

ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid contact with skin, eyes, and clothing.

Keep away from sources of ignition.

Emergency Procedures:

Contain spilled material, collect in suitable and

properly labeled containers.

Environmental Precautions:

Do not allow to reach sewage system or any water

course.

Do not allow to enter ground waters.

Cleanup Procedures:

Pick up excess with inert absorbant material.



Lyden Oil Company

Page 5 of 8 -

PROGUARD Synthetic CD 50W Gear Oil

SDS Number: 702051

7 HANDLING AND STORAGE

Handling Precautions:

Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder

container.

Storage Requirements:

Keep container tightly sealed.
Keep away from sources of ignition.

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

No data available.

Engineering Controls:

All ventilation should be designed in accordance

with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work.

Use safety glasses and gloves.

9 PHYSICAL AND CHEMICAL PROPERTIES

Color: Amber Physical State: Liquid

Odor: Data not available Data not available Odor Threshold: pH: Data not available **Melting Point:** Data not available **Boiling Point:** Data not available **Boiling Range:** Data not available Flash Point: >250° C / >482° F **Evaporation Rate:** Data not available Flammability: Data not available Flammability Limits: Data not available



Lyden Oil Company

Page **6** of **8** -

PROGUARD Synthetic CD 50W Gear Oil

SDS Number: 702051

Vapor Pressure:

Vapor Density:

Relative Density:

Solubilities:

Partition Coefficient:

Auto-Ignition Temperature:

Data not available

Viscosity: 18 mm²/sec (kinematic at 100° C)

10 STABILITY AND REACTIVITY

Stability:

Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.

Conditions to Avoid:

Extreme temperature, sparks, open flame, and

direct sunlight.

Hazardous Reactions:

No known hazardous reactions.

Incompatible Materials:

No further relevant information available.

Decomposition Products:

Hazardous decomposition products are not

expected to form.

11 TOXICOLOGICAL INFORMATION

Routes of Exposure:

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.



Lyden Oil Company

Page **7** of **8** —

PROGUARD Synthetic CD 50W Gear Oil

SDS Number: 702051

Exposure Effects:

Repeated skin contact may cause dermatitis or an

oil acne.

Measures of Toxicity:

No test data available.

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be

mutagentic.

12 ECOLOGICAL INFORMATION

Ecological Precautions:

Avoid exposing to the environment.

Ecological Effects:

No specific environmental or aquatic data available.

13 DISPOSAL CONSIDERATIONS

Disposal Methods:

Dispose of waste material in accordance with all

local, state, and federal requirements.

Disposal Containers:

Use properly approved container for disposal.

Special Precautions:

Do not flush to surface waters or drains.

14 TRANSPORT INFORMATION

UN Number:Data not availableUN Shipping Name:Data not availableTransport Hazard Class:Data not availablePacking Group:Data not available



Lyden Oil Company

Page 8	of 8
---------------	-------------

PROGUARD Synthetic CD 50W Gear Oil

SDS Number: 702051

Environmental Hazards:

Data not available

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.

15

REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16

OTHER INFORMATION

Last Revision Date: 02/05/2016

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.