

Lyden Oil Company

Page 1 of 8 -

PROGUARD Synthetic 75W-90 Gear Oil

SDS Number: 710301

PRODUCT AND COMPANY INFORMATION

Product Name: PROGUARD Synthetic 75W-90 Gear Oil

Revision Date: 10/30/2015 SDS Number: 710301

<u>Common Name:</u> Synthetic gear oil 75W-90

<u>CAS Number:</u> Blend <u>Product Code:</u> 710301

Synonyms: Synthetic automotive gear oil

Company Identification:

Manufactured for: LYDEN OIL COMPANY 3711 LeHarps Road Youngstown, OH 44515

For Product Information: 1-330-792-1100 For Emergencies: 1-800-424-9300

CHEMTREC: 1-800-424-9300 or 1-703-527-3887

HAZARDS IDENTIFICATION



Signal Word: WARNING

Hazard Classes/Categories:

Skin irritant, Category 2.

Serious eye irritation, Category 2B.

Hazardous to the aquatic environment, Category chronic 3.



Lyden Oil Company

Page 2 of 8 -

PROGUARD Synthetic 75W-90 Gear Oil

SDS Number: 710301

Hazard Statement(s):

H320: Causes eye irritation. H315: Causes skin irritation.

H412: Harmful to aquatic life with long-lasting effects.

Precaution Statement(s):

P101: If medical advice is needed, have product container or label at

hand.

P102: Keep out of reach of children.

P103: Read label before use.

P273: Avoid release to the environment.

P302+352: IF ON SKIN: Wash with plenty of soap and water. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue

rinsing.

Other Hazard Statement(s):

-NFPA Ratings: Health = 1 Fire = 1 Reactivity = 0

Repeated exposure may cause skin dryness or cracking.

5

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Synthetic base oil	Proprietary	>70
Additives	Proprietary	<20
Alkyl phosphate	Proprietary	<0.5
Long chain alkyl amines	Proprietary	<0.5
Long chain alkyl phosphonate	Proprietary	<0.5

^{*}Any concentration shown as a range is to protect confidentiality or is due to batch variation.



Lyden Oil Company

Page 3 of 8 -

PROGUARD Synthetic 75W-90 Gear Oil

SDS Number: 710301

4

FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give oxygen with rescue breathing or CPR as required and transport to the nearest medical

facility.

Skin Contact:

Flush skin with water, wash with soap and water. Remove

contaminated clothing. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for

additional treatment.

Eye Contact:

Rinse opened eye for several minutes under running water. If

symptoms persist, consult medical attention.

Ingestion:

Rinse mouth with water. If symptoms develop, obtain medical

attention.

Symptoms and Effects, both acute and delayed:

No further relevent data available.

Recommended Actions:

Treat symptomatically. Call a doctor or poison

control center for guidance.

5

FIRE FIGHTING MEASURES

Recommended Fire-Extinguishing Equipment:

Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters.



Lyden Oil Company

Page **4** of **8** —

PROGUARD Synthetic 75W-90 Gear Oil

SDS Number: 710301

Possible Hazards During a Fire:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Recommendations to Firefighters:

Proper protective equipment including breathing

apparatus.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid contact with skin, eyes, and clothing. Avoid

breathing vapors.

Keep away from sources of ignition.

Emergency Procedures:

Contain spilled material, collect in suitable and

properly labled containers.

Environmental Precautions:

Do not allow to reach sewage system or any water

course.

Do not allow to enter ground waters.

Cleanup Procedures:

Pick up excess with inert absorbant material. Treat contaminated absorbent same as spilled product.



Lyden Oil Company

Page 5 of 8 -

PROGUARD Synthetic 75W-90 Gear Oil

SDS Number: 710301

HANDLING AND STORAGE

Handling Precautions:

Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder

container.

Storage Requirements:

Keep container tightly sealed.
Keep away from sources of ignition.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

-1-Decene, homopolymer, hydrogenated:

ACGIH TWA – 5mg/m³ (oil mist) ACGIH STEL - 10mg/m³ (oil mist) OSHA TWA – 5mg/m³ (oil mist)

Engineering Controls:

All ventilation should be designed in accordance

with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work.

Use safety glasses and gloves.

PHYSICAL AND CHEMICAL PROPERTIES

Color: Dark Amber Physical State: Liquid Odor: Petroleum

Odor Threshold:

pH:

Data not available

Melting Point:

Data not available

Data not available

Data not available

Boiling Point:

Data not available

Data not available

Data not available



Lyden Oil Company

Page 6 of 8 -

PROGUARD Synthetic 75W-90 Gear Oil

SDS Number: 710301

Flash Point: 170° C / 338° F (COC Method)

Evaporation Rate:

Flammability:

Data not available

Vapor Pressure:

Data not available

Data not available

Data not available

Relative Density: 0.89-0.91 (where water = 1)

Solubilities: Insoluble in water
Partition Coefficient: Data not available
Auto-Ignition Temperature: Data not available
Decomposition Temperature: Data not available

Viscosity: 116-298 mm²/sec (kinematic at 40° C)

10 STABILITY AND REACTIVITY

Stability:

Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.

Conditions to Avoid:

Extreme temperature, sparks, open flame, and

direct sunlight.

Hazardous Reactions:

No known hazardous reactions.

Incompatible Materials:

Strong oxidizers and strong reducing agents.

Decomposition Products:

Hazardous decomposition products are not

expected to form.



Lyden Oil Company

Page **7** of **8** -

PROGUARD Synthetic 75W-90 Gear Oil

SDS Number: 710301

11 TOXICOLOGICAL INFORMATION

Routes of Exposure:

Skin and eye contact are the primary routes of exposure although exposure may occur following

accidental ingestion.

Exposure Effects:

Repeated skin contact may cause dermatitis or an

oil acne.

Measures of Toxicity:

No test data available.

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be

mutagentic.

12 ECOLOGICAL INFORMATION

Ecological Precautions:

Avoid exposing to the environment.

Ecological Effects:

No specific environmental or aquatic data available.

13 DISPOSAL CONSIDERATIONS

Disposal Methods:

Dispose of waste material in accordance with all

local, state, and federal requirements.

Disposal Containers:

Use properly approved container for disposal.

Special Precautions:

Do not flush to surface waters or drains.



Lyden Oil Company

Page 8 of 8 -

PROGUARD Synthetic 75W-90 Gear Oil

SDS Number: 710301

14 TRANSPORT INFORMATION

UN Number:Data not availableUN Shipping Name:Data not availableTransport Hazard Class:Data not availablePacking Group:Data not available

Environmental Hazards:

Data not available

Bulk Transport Guidance:

Data not available

Special Precautions:

Not regulated by DOT.

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 OTHER INFORMATION

Last Revision Date: 10/30/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.