

Lyden Oil Company

Page **1** of **7** —

1

## **PROGUARD SPARKUT SC**

SDS Number: 809243

### PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD SPARKUT SC
Revision Date:	09/24/2015
SDS Number:	809243
Common Name:	Hydrotreated heavy naphthenic oil
CAS Number:	Blend
Product Code:	809243
<u>Synonyms:</u>	Machining, grinding, and cutting lubricant

#### **Company Identification:**

<i>Manufactured for:</i> LYDEN OIL COMPANY 3711 LeHarps Road Youngstown, OH 44515	
For Product Information:	1-330-792-1100
For Emergencies:	1-800-424-9300
CHEMTREC:	1-800-424-9300 or 1-703-527-3887

### 2 HAZARDS IDENTIFICATION

Signal Word:	None
Hazard Classes/Categories:	None
Hazard Statement(s):	None
Precaution Statement(s):	P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use.



Lyden Oil Company

Page **2** of **7** –

## **PROGUARD SPARKUT SC**

SDS Number: 809243

Other Hazard Statement(s):

-NFPA Ratings: Health = 1 Fire = 1 Reactivity = 0

Repeated exposure may cause skin dryness or cracking.

3

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>80

\*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4	FIRST AID MEASURES

#### **Description of First Aid Measures:**

Inhalation:	If symptoms develop, move victim to fresh air and keep in a position comfortable for breathing. If symptoms persist, obtain medical attention.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.
Eye Contact:	Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult medical attention.
Ingestion:	Rinse mouth with water. If symptoms develop, obtain medical attention.



Lyden Oil Company

SDS Number: 809243

Page 3 of 7 —

PROGUARD	SPARKUT SC
----------	------------

Symptoms and Effects, both acute and delayed: No further relevent data available. **Recommended Actions:** Treat symptomatically. Call a doctor or poison control center for guidance. 5 FIRE FIGHTING MEASURES Recommended Fire-Extinguishing Equipment: Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective in fighting an oil fire unless used by experienced fire fighters. Possible Hazards During a Fire: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. **Recommendations to Firefighters:** No special measures required. 6 ACCIDENTAL RELEASE MEASURES **Personal Precautions:** Avoid contact with skin, eyes, and clothing. Keep away from sources of ignition. **Emergency Procedures:** Contain spilled material, collect in suitable and properly labled containers.



Lyden Oil Company

Page <b>4</b> of <b>7</b>	
SDS Number: 809243	PROGUARD SPARKUT SC
Environmental Precautions:	
	Do not allow to reach sewage system or any water
	course. Do not allow to enter ground waters.
	Do not allow to enter ground waters.
Cleanup Procedures:	
	Pick up excess with inert absorbant material.
7 HANDLING A	ND STORAGE
Handling Precautions:	
<u></u>	Handle with care and avoid spillage on the floor.
	Do not cut, weld, drill, grind, braze, or solder
	container.
Storage Requirements:	
	Keep container tightly sealed.
	Keep away from sources of ignition.
8 EXPOSURE C	ONTROLS / PERSONAL PROTECTION
Exposure Limits:	
-64742-	52-5 Distillates (petroleum), hydrotreated heavy naphthenic (>90%):
ACGIH <sup>-</sup>	۲LV – Short-term value: 10mg/m³
	rm value: 5mg/m <sup>3</sup>
OSHA P	EL – Long-term value: 5mg/m³
Engineering Controls:	
	All ventilation should be designed in accordance
	with OSHA standard (29 CFR 1910.94).
Personal Protective Equipment	:
	. Wash hands before breaks and at the end of work.
	Use safety glasses and gloves.



Lyden Oil Company

SDS Number: 809243

Page 5 of 7 –

9

## PROGUARD SPARKUT SC

Color:	Amber
Physical State:	Liquid
Odor:	Characteristic
Odor Threshold:	Data not available
pH:	Data not available
Melting Point:	Data not available
Boiling Point:	>500° F
Boiling Range:	Data not available
Flash Point:	380° F
Evaporation Rate:	<1 (where Butyl Acetate - 1)
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	0.9055
Solubilities:	Insoluble in water
Partition Coefficient:	Data not available
Auto-Ignition Temperature:	Data not available
Decomposition Temperature:	Data not available
Viscosity:	26 mm²/sec (kinematic at 40° C)

PHYSICAL AND CHEMICAL PROPERTIES

10	STABILITY AND REACTIVITY	
<u>Stability:</u>		Stable under normal conditions.
<u>Reactivity:</u>		Not reactive under normal conditions.
Conditions to Av		Extreme temperature, sparks, open flame, and direct sunlight.
Hazardous React		No known hazardous reactions.
Incompatible Ma		Strong oxidizers and strong reducing agents.



# Safety Data Sheet

Lyden Oil Company

Page 6 of 7	PROGUARD SPARKUT SC
SDS Number: 809243	PROGUARD SPARKUT SC
Decomposition Products:	Oxides of carbon, sulfur, hydrogen, and hydrogen chloride.
11 TOXICOLOGICAL INFORMATIO	N
Routes of Exposure:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Exposure Effects:	Repeated skin contact may cause dermatitis or an oil acne.
Measures of Toxicity:	No test data available.
Carcinogenic/Mutagenic Precautions:	Non-carcinogenic and not expected to be mutagentic.
12 ECOLOGICAL INFORMATION	
Ecological Precautions:	Avoid exposing to the environment.
Ecological Effects: No specific environmenta	l or aquatic data available.
13 DISPOSAL CONSIDERATIONS	
Disposal Methods:	Dispose of waste material in accordance with all local, state, and federal requirements.
Disposal Containers:	



Lyden Oil Company

Page 7 of 7 —

## **PROGUARD SPARKUT SC**

### SDS Number: 809243

Special Precautions:

Do not flush to surface waters or drains.

14	TRANSPORT	INFORMATION	
<u>UN Number:</u> <u>UN Shipping Nar</u> <u>Transport Hazar</u> <u>Packing Group:</u>		Data not available Lubricating Oil, N.O Data not available Data not available	.S.
Environmental H	lazards:		Data not available
Bulk Transport G	<u>Buidance:</u>		Data not available
Special Precaution	ons:		Not regulated by DOT.

### 15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16 OTHER INFORMATION
----------------------

### Last Revision Date: 09/24/2015

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.