

Lyden Oil Company

Page **1** of **8** —

1

2

PROGUARD Blitz Kleen

SDS Number: 901153

PRODUCT AND COMPANY INFORMATION

Product Name:	PROGUARD Blitz Kleen
Revision Date:	01/21/2016
SDS Number:	901153
Common Name:	Alkaline Cleaning Solution
CAS Number:	Blend
Product Code:	901153
<u>Synonyms:</u>	Cleaner/Degreaser/Pre-Soak

Company Identification:

Manufactured for:LYDEN OIL COMPANY3711 LeHarps DriveYoungstown, OH 44515For Product Information:1-330-792-1100For Emergencies:1-800-424-9300CHEMTREC:1-800-424-9300 or 1-703-527-3887

HAZARDS IDENTIFICATION



Signal Word:

WARNING

Hazard Classes/Categories:

Skin irritant, Category 2. Serious eye irritation, Category 2A. Acute toxicity, Oral category 3.



Lyden Oil Company

Page 2 of 8 -**PROGUARD Blitz Kleen** SDS Number: 901153 Hazard Statement(s): H302: Harmful if swallowed. H315: Causes skin irritation. H319: Causes serious eye irritation. Precaution Statement(s): P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P103: Read label before use. P262: Do not get in eyes, on skin, or on clothing. P280: Wear protective gloves/protective clothing/eye protection/face protection. P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor. P302+352: IF ON SKIN: Wash with plenty of water for several minutes. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. P337+313: If eye irritation persists get medical advice/attention. Other Hazard Statement(s): -NFPA Ratings: Health = 2Fire = 0Reactivity = 0**COMPOSITION / INFORMATION ON INGREDIENTS** 3

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Water	7732-18-5	>60
2-butoxyethanol	111-76-2	1-5
Sodium Metasilicate	6834-92-0	1-5
Tetra Sodium EDTA	64-02-8	1-5
Surfactant Blend	Proprietary	N/A
D'Limonene	5989-27-5	0.5-1



Lyden Oil Company

SDS Number: 901153

Page 3 of 8 -

PROGUARD Blitz Kleen

*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4	FIRST AID MEA	SURES
Description of Fi	rst Aid Measures	
Inhalatic	on:	Ensure supply of fresh air.
Skin Cor	itact:	Remove all contaminated clothing immediately. Rinse area for several minutes with water.
Eye Con	tact:	Rinse cautiously with water for a few minutes. Remove contact lenses if any then continue flushing.
Ingestio	n:	Do not induce vomiting. If person is conscious give 1-2 glasses of water and seek medical attention.
Symptoms and E	ffects, both acute	e and delayed: No further relevent data available.
Recommended A	Actions:	Treat symptomatically. Call a doctor or poison control center for guidance.
5	FIRE FIGHTING	MEASURES
Recommended F	Fire-Extinguishing	<u>Equipment:</u> Use water, dry powder, foam, or carbon dioxide fire extinguishers.
Possible Hazards	During a Fire:	None known.



PROGUARD Blitz Kleen

Lyden Oil Company

SDS Number: 901153

Page 4 of 8 -

Recommendations to Firefighters:

Proper protective equipment including breathing apparatus.

6 ACCIDENTAL RELEASE MEASU	RES
Personal Precautions:	
	Avoid eye contact. Avoid repeated or prolonged
	skin contact.
	Personal protective equipment must be worn.
	Avoid contact with skin, eyes or clothing.
Emergency Procedures:	
	Contain spilled material, collect in suitable and
	properly labeled containers.
Environmental Precautions:	
	Do not allow to reach sewage system or any water course.
	Do not allow to enter ground waters.
<u>Cleanup Procedures:</u>	
<u></u>	Absorb with liquid-binding material (sand,
	diatomite, acid binders, universal binders, sawdust).
7 HANDLING AND STORAGE	

Handling Precautions:	
	Use with adequate ventilation. Avoid breathing dusts, mists, and vapors. Do not get in eyes, on skin, or on clothing. Wear eye protection and protective clothing . Wash thoroughly after handling.
Storage Requirements:	
	Keep container tightly sealed and stored in a dry, cool place. Keep away from sources of ignition.



Lyden Oil Company

Page 5 of 8 -

PROGUARD Blitz Kleen

SDS Number: 901153

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

-2-butoxyethanol:

ACGIH TLV: 20 ppm, 8 hours (all forms) OSHA PEL TWA: 240 mg/m³ 8 hours (skin); TWA: 50 ppm, 8 hours (Skin)

Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Keep away from foodstuffs, beverages, and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with eyes and skin. Use safety glasses and gloves.

9

PHYSICAL AND CHEMICAL PROPERTIES

Color:	Purple
Physical State:	Liquid
Odor:	Citrus / Ether like
Odor Threshold:	Data not available
pH:	12.5-13
Melting Point:	<32° F
Boiling Point:	>212° F
Boiling Range:	Data not available
Flash Point:	>200° F
Evaporation Rate:	Data not available
Flammability:	Data not available
Flammability Limits:	Data not available
Vapor Pressure:	Data not available
Vapor Density:	Data not available
Relative Density:	1.01-1.03
Solubilities:	Soluble in water
Partition Coefficient:	Data not available



PROGUARD Blitz Kleen

Lyden Oil Company

SDS Number: 901153

Page 6 of 8 -

11

Auto-Ignition Temperature: Decomposition Temperature: Viscosity: Data not available Data not available Data not available

10	STABILITY AND REACTIVITY	
<u>Stability:</u>		Stable under normal conditions.
<u>Reactivity:</u>		Not reactive under normal conditions.
Conditions to Av	<u>void:</u>	None known.
Hazardous Reac	<u>tions:</u>	No known hazardous reactions.
Incompatible Ma	aterials:	Strong oxidizers.
Decomposition I	<u>Products:</u>	Hazardous decomposition products are not expected to form.

TOXICOLOGICAL INFORMATION

Routes of Exposure:	
	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Exposure Effects:	
	Skin:
	Prolonged or repeated contact with strong forms may remove natural oils leading to dryness or rash. Eye:
	Produces rapid serious eye irritation.



Page 7 of 8 -

Safety Data Sheet

Lyden Oil Company

PROGUARD Blitz Kleen SDS Number: 901153 Ingestion: May be harmful to mucous membranes, mouth, throat and stomach. Inhalation: Concentrated mists may cause discomfort, cough or dizziness. Measures of Toxicity: -2-butoxyethanol: Oral: LD50 (rat): 470 mg/kg Dermal: LD50 (rabbit): 220 mg/kg Inhilation: LC50 (rat): 450 mg/L, 4 hours Carcinogenic/Mutagenic Precautions: Non-carcinogenic and not expected to be mutagentic. **ECOLOGICAL INFORMATION** 12 **Ecological Precautions:** Avoid exposing to the environment. **Ecological Effects:** No specific environmental or aquatic data available. **DISPOSAL CONSIDERATIONS** 13 **Disposal Methods:** Dispose of waste material in accordance with all local, state, and federal requirements. **Disposal Containers:** Use properly approved container for disposal. **Special Precautions:** Do not flush to surface waters or drains. Hish levels of surfactants and increased pH levels are harmful

to aquatic life.



PROGUARD Blitz Kleen

Lyden Oil Company

SDS Number: 901153

Page 8 of 8 -

14 TRANSPORT INFORMATION UN Number: Data not available **UN Shipping Name:** Data not available Transport Hazard Class: Data not available Packing Group: Data not available **Environmental Hazards:** Data not available **Bulk Transport Guidance:** Data not available **Special Precautions:** Not regulated by DOT.

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

16	OTHER INFORMATION

Last Revision Date: 01/21/2016

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.