

Lyden Oil Company

Page 1 of 9 -

PROGUARD Windshield Washer Fluid Pre-Mix (-50)

SDS Number: 901252

PRODUCT AND COMPANY INFORMATION

Product Name: PROGUARD Windshield Washer Fluid Pre-Mix (-50)

<u>Revision Date:</u> 01/26/2016 <u>SDS Number:</u> 901252

<u>Common Name:</u> Windshield washer fluid

<u>CAS Number:</u> Blend <u>Product Code:</u> 901252

Synonyms: Alcohol based cleaner

Company Identification:

Manufactured for: LYDEN OIL COMPANY 3711 LeHarps Drive Youngstown, OH 44515

For Product Information: 1-330-792-1100 For Emergencies: 1-800-424-9300

CHEMTREC: 1-800-424-9300 or 1-703-527-3887

2 HAZARDS IDENTIFICATION



Signal Word: DANGER

Hazard Classes/Categories:

Flammable liquid, Category 3. Acute toxicity, Oral category 5. Acute toxicity, Dermal category 5.



Lyden Oil Company

Page 2 of 9 -

PROGUARD Windshield Washer Fluid Pre-Mix (-50)

SDS Number: 901252

Acute toxicity, Inhalation category 5.

Specific target organ toxicity – single exposure, Category 1.

Hazard Statement(s):

H226: Flammable liquid and vapor.

H303: May be harmful if swallowed.

H333: May be harmful if inhaled.

H313: May be harmful in contact with skin.

H370: Causes damage to organs-liver, kidneys, central nervous

system and optic nerve.

Precaution Statement(s):

P101: If medical advice is needed, have product container or label at

hand.

P102: Keep out of reach of children.

P103: Read label before use.

P260: Do not breathe mist.

P280: Wear protective gloves/protective clothing/eye protection/face

protection.

P362: Take off contaminated clothing.

P363: Wash contaminated clothing before reuse.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER or

doctor.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue

rinsing.

P403: Store in a well ventilated place.

P401: Store away from heat and ignition sources.

P411: Store at temperatures not exceeding 30°C.

P420: Store away from oxidizing materials and strong acids.

P501: Dispose of contents/container in accordance with

local/regional/national/international regulation.

Other Hazard Statement(s):

-NFPA Ratings:

Health = 1

Fire = 3

Reactivity = 0



Lyden Oil Company

Page 3 of 9 -

PROGUARD Windshield Washer Fluid Pre-Mix (-50)

SDS Number: 901252

3

COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Methanol	67-56-1	40-50

^{*}Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4

FIRST AID MEASURES

Description of First Aid Measures:

Inhalation:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.

racility

Skin Contact:

Flush skin with water, wash with soap and water. Remove

contaminated clothing. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for

additional treatment.

Eye Contact:

Can cause irritation to eyes. Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult medical attention.

Ingestion:

Call a poison center or physician. Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable

for breathing. DO NOT induce vomiting.



Lyden Oil Company

Page **4** of **9** —

PROGUARD Windshield Washer Fluid Pre-Mix (-50)

SDS Number: 901252

Symptoms and Effects, both acute and delayed:

Can cause irritation to eyes and mucous membranes. Sore throat, shortness of breath, coughing and congestion. Skin irritation, itching, dermatitis. Irritation to mucous membranes.

Recommended Actions:

Treat symptomatically. Call a doctor or poison

control center for guidance.

5 FIRE FIGHTING MEASURES

Recommended Fire-Extinguishing Equipment:

Use dry powder, foam, or carbon dioxide fire extinguishers. Water spray may be used for larger

fires.

Possible Hazards During a Fire:

Hazardous combustion products may include

carbon oxides.

Recommendations to Firefighters:

Proper protective equipment including breathing

apparatus.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid contact with skin, eyes, and clothing.

Keep away from sources of ignition, direct sunlight,

and high heat.

Emergency Procedures:

Contain spilled material, collect in suitable and

properly labled containers.



Lyden Oil Company

Page **5** of **9** -

PROGUARD Windshield Washer Fluid Pre-Mix (-50)

SDS Number: 901252

Environmental Precautions:

Do not allow to reach sewage system or any water

course.

Do not allow to enter ground waters.

Cleanup Procedures:

Pick up excess with inert absorbant material. Treat contaminated absorbent same as spilled product.

Ventillate area of spill.

7 HANDLING AND STORAGE

Handling Precautions:

Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder

container.

Storage Requirements:

Keep container tightly sealed.

Keep away from sources of ignition and heat.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

-67-56-1 Methanol (40-50%):

ACGIH TWA – 200 ppm ACGIH STEL – 250 ppm OSHA TWA – 260 mg/m³

Engineering Controls:

All ventilation should be designed in accordance

with OSHA standard (29 CFR 1910.94).

Personal Protective Equipment:

Wash hands before breaks and at the end of work.

Use safety glasses and gloves.



Lyden Oil Company

Page 6 of 9 -

PROGUARD Windshield Washer Fluid Pre-Mix (-50)

SDS Number: 901252

PHYSICAL AND CHEMICAL PROPERTIES

Color: Blue
Physical State: Liquid
Odor: Alcohol

Odor Threshold: Data not available pH: Data not available

Melting Point: <-30° F

Boiling Point: Data not available
Boiling Range: Data not available

Flash Point: <91° F

Evaporation Rate: >1 (where Butyl Acetate - 1)

Flammability: Data not available Flammability Limits: Data not available Vapor Pressure: Data not available

Vapor Density: <1 (Air = 1)

Relative Density: Data not available

Solubilities: Completely soluble in water

Partition Coefficient:

Auto-Ignition Temperature:

Decomposition Temperature:

Decomposition Temperature:

Data not available

Data not available

Data not available

Data not available

10 STABILITY AND REACTIVITY

Stability:

Stable under normal conditions.

Reactivity:

Not reactive under normal conditions.

Conditions to Avoid:

Elevated temperatures, sparks, open flame, and

direct sunlight.

Hazardous Reactions:

No known hazardous reactions.



Lyden Oil Company

Page **7** of **9** —

PROGUARD Windshield Washer Fluid Pre-Mix (-50)

SDS Number: 901252

Incompatible Materials:

Strong oxidizers, strong acids, and strong bases.

Decomposition Products:

Oxides of carbon, and hydrogen.

11 TOXICOLOGICAL INFORMATION

Routes of Exposure:

Skin and eye contact are the primary routes of exposure although exposure may occur following

accidental ingestion.

Exposure Effects:

Repeated skin contact may cause dermatitis. Exposure to eyes may cause redness and blurred vision. Harmful if swallowed, may cause burns to

mouth and esophagus.

Measures of Toxicity:

Component Acute Toxicity Estimates:

Methanol:

Oral LD50: 7300 mg/kg (rat) Dermal LD50: 15800 mg/kg

Inhalative LC50: 87.5 mg/l (6 hours) (rat)

Carcinogenic/Mutagenic Precautions:

Non-carcinogenic and not expected to be

mutagentic.

12 ECOLOGICAL INFORMATION

Ecological Precautions:

Avoid exposing to the environment.



Lyden Oil Company

Page **8** of **9** —

PROGUARD Windshield Washer Fluid Pre-Mix (-50)

SDS Number: 901252

Ecological Effects:

No specific environmental or aquatic data available.

13 DISPOSAL CONSIDERATIONS

<u>Disposal Methods:</u>

Dispose of waste material in accordance with all

local, state, and federal requirements.

Disposal Containers:

Use properly approved container for disposal.

Special Precautions:

Do not flush to surface waters or drains.

14 TRANSPORT INFORMATION

UN Number: UN 1993

UN Shipping Name: Flammable Liquids, N.O.S. (Methanol)

Transport Hazard Class: 3
Packing Group: III

Environmental Hazards:

Data not available

Bulk Transport Guidance:

Reportable Quantity: 5000 pounds

Special Precautions:

Placard: FLAMMABLE

15 REGULATORY INFORMATION

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.



Lyden Oil Company

Page 9 of 9 -

PROGUARD Windshield Washer Fluid Pre-Mix (-50)

SDS Number: 901252

16

OTHER INFORMATION

Last Revision Date: 01/26/2016

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.